

E DIN EN ISO 15118-20:2022-03 (E)

Erscheinungsdatum: 2022-02-18

Road vehicles - Vehicle to grid communication interface - Part 20: 2nd generation network and application protocol requirements (ISO/FDIS 15118-20:2022); English version prEN ISO 15118-20:2022, only on CD-ROM

Contents	Page
1 Scope	1
2 Normative references	1
3 Terms and definitions	4
4 Abbreviated terms	11
5 Conventions	14
5.1 Definition of OSI based services	14
5.2 Requirement structure	14
5.3 Usage of references	15
5.4 Notation used for XML schema diagrams.....	15
6 Document overview.....	15
7 Basic requirements for V2G communication	16
7.1 General information	16
7.2 Service primitive concept of OSI layered architecture.....	17
7.2.1 Overview.....	17
7.2.2 Syntax of service primitives.....	17
7.3 Security concept.....	18
7.3.1 General	18
7.3.2 Certificate and key management	20
7.3.3 Number of root certificates and root validity	32
7.3.4 Support and application of TLS	34
7.3.5 Firewall	34
7.3.6 Protection of the cryptographic keys.....	35
7.3.7 Random number generation	36
7.4 V2G communication states and data link handling	38
7.5 Data link layer	42
7.5.1 Data link layer security for WLAN.....	43
7.6 Network link layer.....	48
7.6.1 General	48
7.6.2 Applicable RFCs, limitations and protocol parameter settings.....	48
7.6.3 IP addressing	50
7.7 Transport layer	50
7.7.1 Transmission control protocol (TCP).....	50
7.7.2 User datagram protocol (UDP).....	51
7.7.3 Transport layer security (TLS)	52
7.8 V2G transfer protocol.....	75
7.8.1 General information	75
7.8.2 Supported ports.....	75
7.8.3 Protocol data unit.....	76
7.9 Presentation layer	80
7.9.1 XML and efficient XML interchange (EXI)	80
7.9.2 Message security.....	83
7.10 Application layer.....	105
7.10.1 SECC discovery protocol	106
8 Application layer messages	117
8.1 General information and definitions.....	117
8.2 Protocol handshake definition.....	117
8.2.1 Handshake sequence.....	118
8.2.2 Message definition supportedAppProtocolReq and supportedAppProtocolRes	119
8.2.3 Semantics description supportedAppProtocol messages	120
8.2.4 Message examples	121
8.3 V2G message definition.....	122
8.3.1 Overview.....	122
8.3.2 General	123
8.3.3 Header definition	123
8.3.4 Request and response definitions.....	126

8.3.5	Complex data types	215
8.4	Service selection.....	320
8.4.1	General.....	320
8.4.2	General description of configuration parameters	321
8.4.3	Selection of service and service parameters.....	322
8.5	V2G communication timing	330
8.5.1	Overview	330
8.5.2	Common	330
8.5.3	DC service	331
8.5.4	Message sequence and communication session	331
8.5.5	Session setup and ready to charge	337
8.5.6	V2G message synchronization for AC and DC with IEC 61851-1 signalling	341
8.5.7	V2G message synchronization with IEC 61980-2 signalling for WPT	348
8.6	Message sequencing and error handling.....	348
8.6.1	Overview	348
8.6.2	Basic definitions for error handling.....	348
8.6.3	ResponseCode handling.....	349
8.6.4	Request-response message sequence requirements	359
8.6.5	Multiplexed communication	383
8.6.6	Message sequence diagrams	385
Annex A	(normative) Schema definition	391
Annex B	(normative) Certificate profiles	392
B.1	Overview	392
B.2	General.....	395
B.2.1	Mandatory versus optional.....	395
B.2.2	Critical versus non-critical.....	397
B.2.3	Common requirements for all certificate profiles	399
B.3	V2G root CA certificate profiles	400
B.3.1	Based on curves as defined by [V2G20-2674]	400
B.3.2	Based on curves as defined by [V2G20-2319]	401
B.4	Charge point operator certificate profiles	403
B.4.1	Based on curves as defined by [V2G20-2674]	403
B.4.2	Based on curves as defined by [V2G20-2319]	405
B.4.3	Common requirements for charge point operator certificate profiles	406
B.5	Certificate provisioning service certificate profiles	407
B.5.1	Based on curves as defined by [V2G20-2674]	407
B.5.2	Based on curves as defined by [V2G20-2319]	408
B.5.3	Common requirements for certificate provisioning service certificate profiles	410
B.6	e-Mobility service provider certificate profiles	410
B.6.1	Based on curves as defined by [V2G20-2674]	410
B.6.2	Based on curves as defined by [V2G20-2319]	413
B.6.3	Common requirements for e-mobility service provider certificate profiles	416
B.7	OEM provisioning certificate profiles.....	418
B.7.1	Based on curves as defined by [V2G20-2674]	418
B.7.2	Based on curves as defined by [V2G20-2319]	421
B.7.3	Common requirements for OEM provisioning certificate profiles	424
B.8	Vehicle certificate profiles	425
B.8.1	Based on curves as defined by [V2G20-2674]	425
B.8.2	Based on curves as defined by [V2G20-2319]	427
B.8.3	Common requirements for vehicle certificate profiles	429
B.9	Cross certificate & OCSP signer certificate profiles.....	430
B.9.1	Based on curves as defined by [V2G20-2674]	430
B.9.2	Based on curves as defined by [V2G20-2319]	432
B.9.3	Common requirements for cross certificate & OCSP signer certificate profiles	434
B.10	Private environment certificate profiles	435
B.10.1	Based on curves as defined by [V2G20-2674]	435
B.10.2	Based on curves as defined by [V2G20-2319]	437
B.10.3	Common requirements for private environment certificate profiles.....	439
Annex C	(normative) Specification of identifiers	441

C.1	e-Mobility authentication identifier (EMAID).....	441
C.1.1	EMAID syntax.....	441
C.2	Provisioning certificate identifier (PCID)	441
C.2.1	PCID syntax.....	441
C.2.2	PCID semantics	442
C.3	Supply equipment communications controller identifier (SECCID)	442
C.3.1	SECCID syntax.....	442
C.3.2	SECCID semantics	443
C.4	Electric vehicle supply equipment ID (EVSEID)	444
C.4.1	EVSEID syntax	444
C.5	Electric vehicle communication controller ID (EVCCID)	444
C.5.1	EVCCID syntax.....	444
C.5.2	EVCCID semantics	445
C.6	Calculation of the check digit	445
Annex D	(informative) ACDP	447
D.1	Coordinate system definition for ACDP with inverted pantograph	447
D.1.1	Coordinate system definitions	447
Annex E	(informative) Basic PPD for interoperability	449
E.1	Overview.....	449
E.2	RFID implementation (recommended)	449
E.2.1	Functional description	449
Annex F	(informative) Message sequencing for renegotiation	453
F.1	Overview.....	453
F.2	Renegotiation after resuming a V2G communication session	453
Annex G	(informative) Association of VAS client to V2G session.....	455
Annex H	(informative) Application of certificates.....	457
H.1	General information	457
H.1.1	Overview	457
H.1.2	Demands of the OEM	458
H.1.3	Demands of the secondary actors.....	458
H.1.4	Rationale for decisions in this document.....	459
H.1.5	Cross certification	460
H.1.6	Examples of the resulting certificate structure.....	464
H.2	Simplified certificate management in private environment	473
H.2.1	Overview.....	473
H.2.2	Solution for private environments.....	476
H.2.3	Security considerations of using private environment credentials	480
H.3	Solution for emergency and disaster situations.....	480
H.4	Use of OEM provisioning certificates.....	481
H.5	Offline contract certificate installation.....	481
H.5.1	Processes.....	482
H.6	Risks of root CA compromise.....	483
H.7	Security appliances and their associated certificates.....	483
Annex I	(informative) Precision of measurements and tolerances.....	491
Annex J	(informative) Absolute pricing examples	493
J.1	Overview.....	493
J.2	Simple examples	493
J.2.1	Parking fee only	493
J.2.2	Energy fee only.....	493
J.2.3	Energy and taxes.....	494
J.2.4	Minimum and maximum cost	494
J.3	Less simple examples.....	495
J.3.1	Different rates for different days.....	495
J.3.2	Different rates for different power levels	496
J.3.3	Different rates for different power levels including reverse power	496
J.3.4	Overstay after charging finished	497
J.3.5	Stacked prices	498
Bibliography		501