

E DIN EN 18060:2024-04 (E)

Erscheinungsdatum: 2024-03-15

Road vehicles - Rechargeable batteries with internal energy storage - Performance of alkali-ion (Li-Ion, Na-Ion), Pb, NiMH and combined chemistries EV modules and batteries; German and English version prEN 18060:2024

Contents

Page

European foreword	4
Introduction	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	7
4 Abbreviated terms.....	14
5 General requirements	14
5.1 Prerequisites for performance tests.....	14
5.2 Accuracy of measurement equipment and measured values.....	15
6 Requirements.....	15
6.1 Preconditioning cycles.....	15
6.1.1 Purpose.....	15
6.1.2 Test procedure.....	15
6.2 Standard cycle (SC).....	16
6.2.1 Purpose.....	16
6.2.2 Test procedure.....	16
6.3 Capacity (in Ah)	17
6.3.1 Purpose.....	17
6.3.2 Test procedure.....	17
6.3.3 Determination of capacity (in Ah)	17
6.4 Determination of internal resistance (in Ω)	18
6.5 Testing of partly charged DUT	19
6.6 Determination of power (in W)	19
6.7 Determination of energy round trip efficiency (in %)	20
6.8 Determination of nominal power	21
6.9 Beginning of life (BOL) full equivalent cycles (for expected lifetime determination)	21
7 Test report.....	22
Annex A (normative) Simplified requirements for individual battery testing due to change of status (status 'reused' and 'remanufactured')	23
A.1 Preconditioning - Purpose.....	23
A.2 Capacity (in Ah)	23
A.2.1 Purpose.....	23
A.2.2 Test procedure.....	23
A.2.3 Determination of capacity (in Ah)	24

A.3	Determination of internal resistance (in Ω)	24
A.4	Testing of partly charged DUT	24
A.5	Determination of power (in W)	25
A.6	Determination of energy round trip efficiency (in %)	25
Annex ZA (informative)	Relationship between this European Standard and the requirements of Regulation (EU) 2023/1542 of the European Parliament and of the Council of 12 July 2023 concerning batteries and waste batteries, amending Directive 2008/98/EC and Regulation (EU) 2019/1020 and repealing Directive 2006/66/EC aimed to be covered	26
Bibliography	28

