

ISO/TR 14646:2007-10 (E)

Road vehicles - Side impact testing of child restraint systems - Review of background data and test methods, and conclusions from the ISO work as of November 2005

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Accident statistics	1
3	Side impact test methods for cars	4
3.1	European side impact test methods	4
3.2	US side impact test methods	5
3.3	Japanese side impact test method	6
3.4	Australian side impact test method	6
4	Child related properties of car side impact test methods	7
4.1	Boundary conditions for a CRS side impact test procedure	7
4.2	Door intrusion depth	7
4.3	Door intrusion velocity from ECE tests	8
4.4	Door intrusion velocity in car-to-car tests	10
4.5	Struck car acceleration and velocity change	13
4.6	Deformation profiles	14
4.7	Dynamic force-deflection characteristics of door interior	15
4.8	Door window sill height and distance to door trim	16
5	Requirements for the side impact test procedure	17
5.1	Test severity	17
5.2	Validation	18
5.3	Repeatability and reproducibility	18
5.4	Field of application	18
6	Historical overview	18
7	Current side impact test procedures for child restraint systems	20
7.1	ISO/DIS 14646 / TRL test procedure	20
7.2	TNO test procedure	23
7.3	TUB test procedure	23
7.4	ADAC test procedure	23
7.5	Australian Standard AS/NZS 1754 test procedure	23
7.6	Australian CREP test procedure	23
8	Conclusions	24
Annex A (informative)	ISO/DIS 14646-1.2: ISO side impact test procedure for rearward-facing child restraint systems	25
	procedure for forward facing systems	36
Annex C (informative)	Voting results and comments received on ISO/DIS 14646:2003	39
Annex D (informative)	Voting results and comments received on ISO/DIS 14646-1.2:2005	45
Glossary		49
Bibliography		50