

ISO 11012:2009-09 (E)

Heavy commercial vehicles and buses - Open-loop test methods for the quantification of on-centre handling - Weave test and transition test

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and symbols | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Symbols | 2 |
| 4 | Principle | 2 |
| 5 | Variables | 2 |
| 5.1 | Reference system | 2 |
| 5.2 | Variables | 3 |
| 6 | Measuring equipment | 3 |
| 7 | Test conditions | 4 |
| 8 | Test procedure | 4 |
| 8.1 | General | 4 |
| 8.2 | Warm-up | 4 |
| 8.3 | Initial driving condition | 4 |
| 8.4 | Weave test procedure | 4 |
| 8.5 | Transition test procedure | 5 |
| 9 | Data evaluation and presentation of results | 5 |
| 9.1 | General | 5 |
| 9.2 | Time histories | 5 |
| 9.3 | Characteristic values for the weave test | 6 |
| 9.4 | Characteristic values for the transition test | 8 |
| Annex A (normative) | Test report -- General data and test conditions | 11 |
| Annex B (informative) | Calculating the time delay from sinusoidal data | 12 |
| Bibliography | | 14 |