

ISO/TS 22239-2:2009-12 (E)

Road vehicles - Child seat presence and orientation detection system (CPOD) - Part 2: Resonator specification

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	CPOD resonator components	2
5	Coil requirements	2
6	Electrical properties	3
6.1	Digital resonator protocol	3
6.2	Subcarrier bitstream	5
6.3	Modulation	7
6.4	Modulation parameters	16
7	Resonator timing	18
7.1	General	18
7.2	Power-up	18
7.3	Reset	18
7.4	Relevant timing and reset parameters	19
8	Electrical and environmental parameters	20
8.1	Absolute maximum ratings	20
8.2	Operating ranges	21
8.3	Storage conditions	21
9	CPOD resonator compatibility test	21
10	Resonator environmental qualification	22
10.1	Application profile	22
10.2	Common test parameters	23
10.3	Operating states	24
10.4	Parametrical test and parameter checking	24
10.5	Qualification tests	25
10.6	Electromagnetic compatibility (EMC) test	38
10.7	Electrostatic discharge (ESD) test	47
10.8	Magnetic field stress test	50
10.9	Qualification flow chart	51
Annex A (normative) CPOD resonator compatibility test set-up		52
Annex B (normative) CPOD resonator compatibility test parameters		58
Annex C (normative) Continuous parameter check		61
Annex D (normative) CPOD reference resonator		63