

# ISO 8820-4:2010-12 (E)

## Road vehicles - Fuse-links - Part 4: Fuse-links with female contacts (type A) and bolt-in contacts (type B) and their test fixtures

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Marking, labelling and colour coding .....</b>	<b>2</b>
<b>5</b>	<b>Tests and requirements .....</b>	<b>2</b>
5.1	General .....	2
5.2	Test sequence .....	4
5.3	Test cable sizes .....	4
5.4	Voltage drop .....	5
5.5	Transient current cycling .....	6
5.6	Environmental condition .....	6
5.7	Operating time-rating .....	6
5.8	Current steps .....	7
5.9	Breaking capacity .....	7
5.10	Strength of terminals .....	7
5.11	Temperature rise .....	8
5.12	Rapid change of temperature with specified transition duration .....	9
<b>6</b>	<b>Dimensions .....</b>	<b>9</b>
6.1	Fuse-links types A1, A2 and A3 .....	9
6.2	Fuse-links type A1S .....	10
6.3	Fuse-links types B1 and B2 .....	11
6.4	Designation .....	12
<b>7</b>	<b>Test fixtures .....</b>	<b>13</b>
7.1	Test fixture for fuse-links types A1, A1S, A2 and A3 .....	13
7.2	Test fixture for fuse-links type B1 .....	14
7.3	Test fixture for fuse-links type B2 .....	15
<b>Annex A (informative)</b>	<b>Tab dimensions for fuse-boxes .....</b>	<b>16</b>