

# DIN ISO 8820-7:2011-05 (E)

## Road vehicles - Fuse-links - Part 7: Fuse-links with tabs (Type G) with rated voltage of 450 V (ISO 8820-7:2007)

---

| Contents                                           | Page |
|----------------------------------------------------|------|
| National foreword .....                            | 3    |
| National Annex NA (informative) Bibliography ..... | 3    |
| 1 Scope .....                                      | 4    |
| 2 Normative references .....                       | 4    |
| 3 Terms and definitions .....                      | 4    |
| 4 Marking, labelling and colour coding .....       | 5    |
| 5 Tests and requirements .....                     | 5    |
| 5.1 General .....                                  | 5    |
| 5.2 Voltage drop .....                             | 7    |
| 5.3 Transient current cycling .....                | 8    |
| 5.4 Environmental conditions .....                 | 8    |
| 5.5 Operating time rating .....                    | 8    |
| 5.6 Current steps .....                            | 9    |
| 5.7 Breaking capacity .....                        | 9    |
| 5.8 Terminal strength .....                        | 9    |
| 6 Dimensions and designation examples .....        | 10   |
| 6.1 Types .....                                    | 10   |
| 6.2 Fuse-links with IR 35 A .....                  | 11   |
| 6.3 Fuse-links with IR 35 A .....                  | 12   |
| 6.4 Designation example .....                      | 12   |
| 7 Test fixture .....                               | 13   |
| 7.1 Test fixture for fuse-links with IR 35 A ..... | 13   |
| 7.2 Test fixture for fuse-links with IR 35 A ..... | 15   |
| Bibliography .....                                 | 17   |