ISO 11519-3:1994-06 (E)

Road vehicles - Low-speed serial data communication - Part 3: Vehicle area network (VAN)

Contents

Page

1 Scope 1
2 Normative references 1
3 Definitions and abbreviations 1
3.1 Definitions 1
3.2 List of abbreviations 3
4 Presentation of architecture 4
4.1 General 4
4.2 Reference to OSI model 5
5 Description of LLC sublayer 6
5.1 LLC service specifications 6
5.2 Error management at LLC level 10
5.3 Error recovery management at LLC level 10
6 Description of the MAC sublayer 10
6.1 Specification of MAC service 10
6.2 Structure of MAC frames 23
6.3 Specification of Medium Access Method (MAC) 42
7 Description of physical layer 48
7.1 Specification of physical service 49
7.2 Encoding/decoding and synchronization sublayer 53
7.3 Line transmitter/receiver 76
7.4 Connector 79
7.5 Communication medium 79
8 Electrical parameters 79
8.1 At LLC sublayer level 79
8.2 At MAC sublayer level 79
8.3 At physical layer level 80
9 Conformance 83
9.1 Conformance at MAC layer level 83
9.2 Conformance at physical layer level: Line transmitter/receiver tests 84

Annexes
A Setup example for Baud Rate Multiplier 89
B Setup example of realization of interface between physical layer and data link layer 90
B.1 Interface position/OSI model 90
B.2 Definition of dialogue signals between binary and electric encoding/decoding sublayers 90
B.3 Coding bit and symbol (see 7.2.3) 90
B.4 Character synchronization 90
B.5 Signals exchange rules between PL1 and PL2 sublayers 96
B.6 Exceptions to this signal exchange rules 96
B.7 Timing diagram for various dialogue signals between PL1 and PL2 sublayers 96