

ISO 15765-2:2011-11 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 2: Transport protocol and network layer services

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	1
4	Conventions	3
5	Document overview	3
6	Network layer overview	5
6.1	General	5
6.2	Services provided by network layer to higher layers	5
6.3	Internal operation of network layer	5
7	Network layer services	7
7.1	General	7
7.2	Specification of network layer service primitives	7
7.3	Service data unit specification	10
8	Transport layer protocol	13
8.1	Protocol functions	13
8.2	SingleFrame transmission	13
8.3	Multiple-frame transmission	13
8.4	Transport layer protocol data units	17
8.5	Protocol control information specification	18
8.6	Maximum number of FC.WAIT frame transmissions (N_WFTmax)	24
8.7	Network layer timing	24
8.8	Interleaving of messages	29
9	Data link layer usage	30
9.1	Data link layer service parameters	30
9.2	Data link layer interface services	30
9.3	Mapping of the N_PDU fields	30
9.4	CAN frame data length code (DLC)	33
Annex A (normative)	Use of normal fixed and mixed addressing with data link layer according to SAE J1939	35
Annex B (normative)	Reserved CAN Ids	38
Bibliography		39