

ISO 11452-4:2011-12 (E)

Road vehicles - Component test methods for electrical disturbances from n arrowband radiated electromagnetic energy - Part 4: Harness excitation methods

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Test conditions | 1 |
| 5 | Test location | 2 |
| 6 | Test instrumentation | 2 |
| 6.1 | BCI test method | 2 |
| 6.2 | TWC test method | 3 |
| 7 | Test set-up | 4 |
| 7.1 | Ground plane | 4 |
| 7.2 | Power supply and AN | 4 |
| 7.3 | Location of the DUT | 4 |
| 7.4 | Length and location of the test harness | 5 |
| 7.5 | Location of the load simulator | 5 |
| 7.6 | Location of the harness excitation | 5 |
| 8 | Test procedure | 10 |
| 8.1 | General | 10 |
| 8.2 | Test plan | 10 |
| 8.3 | Test methods | 10 |
| 8.4 | Test report | 14 |
| Annex A (normative) Calibration configuration (current injection probe calibration) | | 15 |
| Annex B (informative) Test set-up transfer impedance | | 17 |
| Annex C (informative) Artificial network | | 23 |
| Annex D (informative) Grounding configurations | | 25 |
| Annex E (informative) Function performance status classification (FPSC) | | 27 |