

# ISO/TS 19072-4:2012-09 (E)

## Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 4: Pyrotechnic device and harness connector assembly - type 2

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	<b>Scope .....</b>	<b>1</b>
2	<b>Normative references .....</b>	<b>1</b>
3	<b>Terms and definitions .....</b>	<b>1</b>
4	<b>Dimensional features and performance requirements .....</b>	<b>2</b>
4.1	<b>General .....</b>	<b>2</b>
4.2	<b>Retainer and squib holder assembly .....</b>	<b>3</b>
4.3	<b>Codings and polarization .....</b>	<b>3</b>
4.4	<b>Dimensional features and properties for shorting clip function .....</b>	<b>5</b>
4.5	<b>Dimensional features and properties for shorting clip function .....</b>	<b>7</b>
5	<b>Material characteristics .....</b>	<b>7</b>
5.1	<b>Contacts clip contact specifications .....</b>	<b>7</b>
5.2	<b>Retainer .....</b>	<b>7</b>
<b>Annex A (normative) Three-way (with ground) variant of the pyrotechnic device/initiator harness connector assembly .....</b>		<b>8</b>