ISO 17458-5:2013-02 (E)

Road vehicles - FlexRay communications system - Part 5: Electrical physical layer conformance test specification

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 1
3.1 Terms and definitions 1
3.2 Abbreviated terms 2

4 Document reference according to OSI model 3

5 Conventions 4
5.1 General 4
5.2 Notational conventions 4

6 Test environment 4
6.1 Test case architecture 4
6.2 Test method 5
6.3 Test environment 9
6.4 Test topology 9
6.5 Test equipment 27

7 Stress Conditions 34
7.1 Ground shift 34
7.2 Low battery voltage inside operational range 35
7.3 Undervoltage 36
7.4 Dynamic low battery voltage 37
7.5 Dynamic low supply voltage 38
7.6 Failures 41
7.7 Babbling idiot 47
7.8 Dynamic ground shift 47
7.9 EMC 48
7.10 ESD 48
7.11 Temperature tests 48
7.12 Common mode offset 48

8 Parameter List 49
8.1 General 49
8.2 Static test cases 50
8.3 Communication 50
8.4 Host Interface 54
8.5 Mode 55
8.6 Power supply 59
8.7 Environment 61
8.8 Dynamic low battery voltage 62
8.9 Dynamic low supply voltage 62
8.10 Failure 62
8.11 Functional class 65

8.12 Simulation 65

9 Test Cases for Bus Drivers 65
9.1 Configuration 66
9.2 Static test cases 89
9.3 Test cases 97

10 Test cases for Active Stars 563
10.1 General 563
10.2 Configuration 563
10.3 Static test cases 577
10.4 Test cases 584

11 Test cases for Active Stars with communication controller interface 717
11.1 Configuration 717
11.2 Static test cases 724
11.3 Test cases 728

12 Test Cases for Active Stars with host interface 795
12.1 Configuration 795
12.2 Static test cases 800
12.3 Test cases 803

Annex A (normative) FlexRay parameters 922

Bibliography 930