

ISO 17458-5:2013-02 (E)

Road vehicles - FlexRay communications system - Part 5: Electrical physical layer conformance test specification

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, symbols and abbreviated terms | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Abbreviated terms | 2 |
| 4 | Document reference according to OSI model | 3 |
| 5 | Conventions | 4 |
| 5.1 | General | 4 |
| 5.2 | Notational conventions | 4 |
| 6 | Test environment | 4 |
| 6.1 | Test case architecture | 4 |
| 6.2 | Test method | 5 |
| 6.3 | Test environment | 9 |
| 6.4 | Test topology | 9 |
| 6.5 | Test equipment | 27 |
| 7 | Stress Conditions | 34 |
| 7.1 | Ground shift | 34 |
| 7.2 | Low battery voltage inside operational range | 35 |
| 7.3 | Undervoltage | 36 |
| 7.4 | Dynamic low battery voltage | 37 |
| 7.5 | Dynamic low supply voltage | 38 |
| 7.6 | Failures | 41 |
| 7.7 | Babbling idiot | 47 |
| 7.8 | Dynamic ground shift | 47 |
| 7.9 | EMC | 48 |
| 7.10 | ESD | 48 |
| 7.11 | Temperature tests | 48 |
| 7.12 | Common mode offset | 48 |
| 8 | Parameter List | 49 |
| 8.1 | General | 49 |
| 8.2 | Static test cases | 50 |
| 8.3 | Communication | 50 |
| 8.4 | Host Interface | 54 |
| 8.5 | Mode | 55 |
| 8.6 | Power supply | 59 |
| 8.7 | Environment | 61 |
| 8.8 | Dynamic low battery voltage | 62 |
| 8.9 | Dynamic low supply voltage | 62 |
| 8.10 | Failure | 62 |
| 8.11 | Functional class | 65 |

| | | |
|------|---|-----|
| 8.12 | Simulation | 65 |
| 9 | Test Cases for Bus Drivers | 65 |
| 9.1 | Configuration | 66 |
| 9.2 | Static test cases | 89 |
| 9.3 | Test cases | 97 |
| 10 | Test cases for Active Stars | 563 |
| 10.1 | General | 563 |
| 10.2 | Configuration | 563 |
| 10.3 | Static test cases | 577 |
| 10.4 | Test cases | 584 |
| 11 | Test cases for Active Stars with communication controller interface | 717 |
| 11.1 | Configuration | 717 |
| 11.2 | Static test cases | 724 |
| 11.3 | Test cases | 728 |
| 12 | Test Cases for Active Stars with host interface | 795 |
| 12.1 | Configuration | 795 |
| 12.2 | Static test cases | 800 |
| 12.3 | Test cases | 803 |
| | Annex A (normative) FlexRay parameters | 922 |
| | Bibliography | 930 |