ISO 15638-5:2013-06 (E)

Intelligent transport systems - Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) - Part 5: Generic vehicle information

Contents

Page

Foreword vi

Introduction vi

1 Scope 1

2 Conformance 1

3 Normative references 2

4 Terms and definitions 3

5 Symbols (and abbreviated terms) 5

6 General overview and framework 6
6.1 General overview 6
6.1.1 Context 6
6.1.2 ROAM 11

7 System requirements 18
7.1 Communications requirements 18
7.2 TARV-ROAM Security requirements 18
7.3 TARV-ROAM facilities layer requirements 18
7.4 7Host management centre (HMC) requirements 19

8 Generic vehicle data requirements 19
8.1 Data provision 19
8.1.1 Location of on-board data 19
8.1.2 Naming of `Apps' 19
8.1.3 Local data trees 20
8.1.4 C-ITS LDT 20
8.1.5 TARV LDT 20
8.1.6 Recent data archive 21
8.2 Commands for vehicle data 21
8.2.1 GET TARV LDT data 21
8.2.2 GET C-ITS LDT data 22
8.2.3 CREATE core application data 22
8.2.4 GET core application data 24
8.2.5 GET Archive 24
8.3 Presentation of the `basic vehicle data' concept 24
8.3.1 Data format version 24
8.3.2 Message identifier 25
8.3.3 8.3.3 Prime service provider identifier 25
8.3.4 Application service provider identifier 25
8.3.5 Session control data 26
8.3.6 Vehicle unique identifier 27
8.3.7 Vehicle class identification 27
8.3.8 VIN number 27
8.3.9 Propulsion storage type 27

8.3.10 Time and timestamp (UTC sec) 28
8.3.11 Location 28
8.3.12 Error estimation (covariance matrix) 30
8.3.13 Direction of travel 31
8.3.14 Ignition status 32
8.3.15 Other movement sensors 32
8.3.16 IVS identification 32
8.3.17 Manufacturer identification 33
8.3.18 Driver(s) identification 34
8.3.19 Trailer identification 35
8.3.20 Load data 35
8.4 Organisation of the TARV LDT 35

9 Additional data provision options for `core application data' and regulated applications . 37
9.1 General 37
9.2 Additional data options for `core application data' 39
9.2.1 Accelerometer data 39
9.2.2 Gyroscope data 40
9.2.3 Camera/video data 40
9.2.4 Vehicle speed data 40
9.2.5 Alarm status data and records 41
9.3 Distributed directory service (DDS) requirements 42

10 Test requirements 42

11 Marking, labelling and packaging 43

12 Declaration of patents and intellectual property 44

Annex A (informative) Registration provisions of ISO 14816 45

A.1 General rules 45
A.1.1 Registration hierarchy 45
A.1.2 Definition of actors 46

12.1.1 Issuer: 46
12.1.2 Issuer register: 46

A.1.3 Central registration administrator (CRA) 46

12.1.3 General 46
12.1.4 Responsibilities 46

A.2 Application and registration procedures FOR CS1: Issuers 47
A.2.1 Issuer 47
A.2.2 National registration administrator (NRA/I) 48
A.3 Application and registration procedures for CS8: Tax codes 49
A.4 Application and registration procedures for CS2: Manufacturers 49
A.4.1 Application procedure for assignment of a manufacturer Identifier 49
A.4.2 Criteria for approval of an application for an manufacturer identifier 49
A.4.3 Responsibilities of the manufacturer 50
A.4.4 Responsibilities CRA for manufacturer register 50
A.4.5 Register of manufacturers 50
A.5 Costs aspects 51
A.6 Disclaimer 51

Annex B (normative) CVIS 3.4 System Specifications 52

B.1 CVIS Architecture and system specifications Section 3.1 52
B.1.1 CVIS 3.1 OSGiTMframework & lifecycle management 52

12.1.5 CVIS 3.1.2 Application programming interface 54

B.1.2 CVIS 3.2 Distributed directory service 56

C.1 Objectives 64
C.2 Test script 1 LDT Service : Local Data Tree 66

CTP 1.1.1 Instigated LDT using 2G 66

CTP 1.1.2 Interrogated LDT using 2G 68

CTP 1.1.3 Interrogated LDT using 5.9GHz and responding using 2G or 3G 70

CTP 1.2.1 Instigated LDT using 3G 72

CTP 1.2.2 Interrogated at 5.9 GHz and send of LDT using 3G 74

CTP 1.3.1 Instigated LDT using 802.11p (WAVE) 5.9 GHz 76

CTP 1.3.2 Interrogated LDT using 802.11p (WAVE) 5.9 GHz 78

CTP 1.4.1 Instigated LDT using Mesh WiFi 80

CTP 1.4.2 Interrogated LDT using Mesh WiFi 82
C.3 Test script 2 Service : Core Data 84

CTP 2.1.1 Instigated Core Data using 2G 85

CTP 2.1.2 Interrogated Core Data using 2G 87

CTP 2.1.3 Interrogated Core Data using 5.9GHz and responding using 2G or 3G 89

CTP 2.2.1 Instigated Core Data using 3G 91

CTP 2.2.2 Interrogated at 5.9 GHz and send of Core Data using 3G 93

CTP 2.3.1 Instigated Core Data using 802.11p (WAVE) 5.9 GHz 95

CTP 2.3.2 Interrogated Core Data using 802.11p (WAVE) 5.9 GHz 97

CTP 2.4.1 Instigated Core Data using Mesh WiFi 99

CTP 2.4.2 Interrogated Core Data using Mesh WiFi 101

Bibliography 103