

ISO/TS 15638-15:2013-08 (E)

Intelligent transport systems - Framework for collaborative Telematics Applications for Regulated commercial freight Vehicles (TARV) - Part 15: Vehicle location monitoring (VLM)

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Conformance	1
3	Normative references	2
4	Terms and definitions	2
5	Symbols (and abbreviated terms)	7
6.	General overview and framework requirements	8
7.	Requirements for services using generic vehicle data	9
8.	Application services that require data in addition to basic vehicle data	9
8.1	General	9
8.2	Quality of service requirements	9
8.3	Test requirements	9
8.4	Marking, labelling and packaging	10
9.	Common features of regulated TARV application services	10
9.1	General	10
9.2	Common role of the jurisdiction, approval authority, service provider and user	11
9.3	Common characteristics for instantiations of regulated application services	11
9.4	Common sequence of operations for regulated application services	11
9.5	Quality of service	11
9.6	Information security	12
9.7	Data naming content and quality	12
9.8	Software engineering quality systems	12
9.9	Quality monitoring station	12
9.10	Audits	12
9.11	Data access control policy	12
9.12	Approval of IVSs and service providers	12
10.	Vehicle location monitoring (VLM)	12
10.1	TARV VLM service description and scope	12
10.1.1	TARV VLM use case	12
10.1.2	Description of TARV VLM regulated application service	13
10.1.3	Description of TARV 'vehicle location monitoring' (TARV VLM) application service	13
10.2	Concept of operations for TARV VLM	14
10.2.1	General	14
10.2.2	Statement of the goals and objectives of the TARV VLM system	15
10.2.3	Strategies, tactics, policies, and constraints affecting the TARV VLM system	15
10.2.4	Organisations, activities, and interactions among participants and stakeholders for TARV VLM	16

10.2.5	Clear statement of responsibilities and authorities delegated for TARV VLM	17
10.2.6	Equipment required for TARV VLM	17
10.2.7	Operational processes for the TARV VLM system	19
10.2.8	Role of the jurisdiction in TARV VLM	19
10.2.9	Role of the TARV VLM prime service provider	19
10.2.10	Role of the TARV VLM application service provider	19
10.2.11	Role of the TARV VLM user	19
10.2.12	Generic characteristics for all instantiations of the TARV VLM application service	19
10.3	Sequence of operations for TARV VLM	20
10.3.1	General	20
10.4	TARV VLM service elements	22
10.4.1	TARV VLM service element SE1: Establish `Vehicle location monitoring' regulations, requirements, and approval arrangements	22
10.4.2	TARV VLM SE2: Request system approval	22
10.4.3	TARV VLM SE3: User (operator) contracts with prime service provider	22
10.4.4	TARV VLM SE4: User (operator) equips vehicle with a device to read the driver licence (DLR)	22
10.4.5	TARV VLM SE5: User contracts with application service provider	22
10.4.6	TARV VLM SE6: application service provider uploads software into the TARV equipped vehicles of the operator	22
10.4.7	TARV VLM SE7: The driver obtains an electronic drivers licence device (eDL)	22
10.4.8	TARV VLM SE8: Driver use of vehicle routines	23
10.4.9	TARV VLM SE9: Time series or application service instigated recording of vehicle location	23
10.4.10	TARV VLM SE10: `Interrogated' request for vehicle location data	24
10.4.11	TARV VLM SE11: End of session	24
10.5	Generic TARV VLM data naming content and quality	25
10.6	TARV VLM service specific provisions for quality of service	26
10.7	TARV VLM application service specific provisions for test requirements	26
10.8	TARV VLM application specific rules for the approval of IVSs and `Service Providers'	26
11.	Declaration of patents and intellectual property	27
Annex A (normative) Independent testing of the protocols defined in this Part of ISO 15638		28
A.1	Objectives	28
A.2	TEST SCRIPT 7	30
A.3	TEST SCRIPTS AND RESULTS VLM	31
CTP 7.1.1 Instigated Vehicle Location Monitoring using 2G		31
CTP 7.1.2 Interrogated Vehicle Location Monitoring using 2G		34
CTP 7.1.3. Interrogated Vehicle Location Monitoring using 5.9GHz and responding using 2G or 3G		36
CTP 7.2.1 Instigated Vehicle Location Monitoring using 3G		38
CTP 7.2.2 Interrogated at 5.9 GHz and send of Vehicle Location Monitoring using 3G		40
CTP 7.3.1 Instigated Vehicle Location Monitoring using 802.11p (WAVE) 5.9 GHz		42
CTP 7.3.2 Interrogated Vehicle Location Monitoring using 802.11p (WAVE) 5.9 GHz		44
CTP 7.4.2 Interrogated Vehicle Location Monitoring using Mesh WiFi		48
Bibliography		50