ISO 19072-2:2013-09 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Pa rt 2: Test methods and general performance requirements

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Functional characteristics of mated connectors 2
4.1 General 2
4.2 Visual examination 2
4.3 Mating and unmating 2
4.4 Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer 3
4.5 Mechanical strength of the retainer in the squib holder 5
4.6 Combination of temperature/humidity/vibration 5
4.7 Coding 8
4.8 Polarisation 8
4.9 Contact resistance (voltage drop), millivolt test 8
4.10 Insulation resistance 10
4.11 Withstand voltage 10
4.12 Thermal ageing 10
4.13 Opening and closing of the short-circuit 10
4.14 Short-circuit resistance 11
4.15 Rapid change of temperature (thermal shock) 12
4.16 Chemical fluids 12

5 Test sequences 12

Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly 14

Annex B (normative) Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly 16

Annex C (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly 18

Bibliography 19