

ISO 19072-2:2013-09 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Functional characteristics of mated connectors	2
4.1 General	2
4.2 Visual examination	2
4.3 Mating and unmating	2
4.4 Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer	3
4.5 Mechanical strength of the retainer in the squib holder	5
4.6 Combination of temperature/humidity/vibration	5
4.7 Coding	8
4.8 Polarisation	8
4.9 Contact resistance (voltage drop), millivolt test	8
4.10 Insulation resistance	10
4.11 Withstand voltage	10
4.12 Thermal ageing	10
4.13 Opening and closing of the short-circuit	10
4.14 Short-circuit resistance	11
4.15 Rapid change of temperature (thermal shock)	12
4.16 Chemical fluids	12
5 Test sequences	12
Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly	14
Annex B (normative) Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly	16
Annex C (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly	18
Bibliography	19