

ISO 6722-2:2013-12 (E)

Road vehicles - 60 V and 600 V single-core cables - Part 2: Dimensions, test methods and requirements for aluminium conductor cables

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | General | 1 |
| 4.1 | Safety concerns | 1 |
| 4.2 | Temperature classes | 2 |
| 4.3 | Conductors | 2 |
| 4.4 | Tests | 2 |
| 4.5 | General test conditions | 3 |
| 4.6 | Ovens | 3 |
| 4.7 | Representative conductor sizes for testing | 4 |
| 4.8 | Recommended colours | 4 |
| 5 | Tests | 4 |
| 5.1 | Outside cable diameter | 4 |
| 5.2 | Insulation thickness | 5 |
| 5.3 | Conductor diameter and cross-sectional area | 6 |
| 5.4 | Conductor resistance | 8 |
| 5.5 | Withstand voltage | 9 |
| 5.6 | Insulation faults | 9 |
| 5.7 | Insulation volume resistivity | 9 |
| 5.8 | Pressure test at high temperature | 10 |
| 5.9 | Strip force | 10 |
| 5.10 | Low temperature winding | 10 |
| 5.11 | Cold impact | 10 |
| 5.12 | Abrasion test | 10 |
| 5.13 | Long-term heat ageing, 3 000 h | 10 |
| 5.14 | Short-term heat ageing, 240 h | 10 |
| 5.15 | Thermal overload | 10 |
| 5.16 | Shrinkage by heat | 10 |
| 5.17 | Resistance to chemicals | 10 |
| 5.18 | Durability of cable marking | 10 |
| 5.19 | Resistance to ozone | 10 |
| 5.20 | Resistance to hot water | 11 |
| 5.21 | Temperature and humidity cycling | 11 |
| 5.22 | Resistance to flame propagation | 11 |
| Annex A (informative) | Conductor sizes and cable dimensions | 12 |
| Annex B (normative) | Determination of temperature coefficients | 14 |
| Bibliography | | 16 |