

ISO 16844-4:2015-01 (E)

Road vehicles - Tachograph systems - Part 4: CAN interface

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative reference	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	1
5	Physical layer application requirements	2
5.1	General	2
5.2	Bit timing requirements	3
5.2.1	General	3
5.2.2	CAN bit timing requirements for 250 kbit/s	3
5.2.3	CAN bit timing requirements for 500 kbit/s	4
6	Data link layer application requirements	4
6.1	Message frame format	4
6.1.1	General	4
6.1.2	Priority (P) bits	5
6.1.3	Extended data page (EDP) bit	5
6.1.4	Data page (DP) bit	5
6.1.5	PDU format (PF) field	5
6.1.6	PDU specific (PS) field	5
6.1.7	Source address (SA) field	5
6.1.8	Data field	6
6.2	PDU specification	6
6.2.1	Parameter group number (PGN)	6
6.2.2	PDU format	6
6.3	Message types	6
6.3.1	General	6
6.3.2	RQST -- Request	7
6.3.3	ACKM -- Acknowledgment message	8
7	Transport protocol	8
7.1	General	8
7.2	BAM -- Broadcast announce message	9
7.3	TP.DT -- Transport protocol -- Data transfer	9
8	Application layer	10
8.1	General	10
8.2	TD -- Time/Date	10
8.3	VI -- Vehicle identification	11
8.4	VDHR -- High resolution vehicle distance	11
8.5	SERV -- Service information	12
8.6	RESET -- Reset	12
8.7	TCO1 -- Tachograph	13
8.8	DI -- Driver's identification	14
8.9	TDA -- Time/Date adjust	14

8.10	EEC1 -- Electronic engine controller 1	15
8.11	CL -- Cab illumination message	16
8.12	DRTD1 -- Driver 1 driving rest times	16
8.13	DRTD2 -- Driver 2 driving rest times	17
9	Addresses	18
	Bibliography	19