ISO 11898-1:2015-12 (E)

Road vehicles - Controller area network (CAN) - Part 1: Data link layer and physical signalling

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Conformance 1

3 Normative references 2

4 Termsanddefinitions 2

5 Symbols and abbreviated terms 5

6 Basic concepts of CAN 7
6.1 CAN properties 7
6.2 Frames 8
6.3 Bus access method 8
6.4 Information routing 8
6.5 Network flexibility 8
6.6 Data consistency 8
6.7 Remote data request 8
6.8 Error detection 9
6.9 Error signalling and recovery time 9
6.10 ACK 9
6.11 Automatic retransmission 9
6.12 Fault confinement 9
6.13 Error-active 9
6.14 Error-passive 9
6.15 Bus-off 10

7 Layered architecture of CAN 10
7.1 Reference to OSI model 10
7.2 Protocol specification 11
7.3 Format description of services 11
7.3.1 Format description of service primitives 11
7.3.2 Types of service primitives 12
7.4 LLC interface 12

8 Description of LLC sub-layer 12
8.1 General 12
8.2 Services of LLC sub-layer 13
8.2.1 Types of connectionless-mode transmission services 13
8.2.2 Service primitive specification 13
8.3 Functions of LLC sub-layer 18
8.3.1 General 18
8.3.2 Frame acceptance filtering 18
8.3.3 Overload notification 18
8.3.4 Recovery management 19
8.4 Structure of LLC frames 19
8.4.1 General 19

8.4.2 Specification of LLC DF 19
8.4.3 Specification of LLC RF 20
8.5 Limited LLC frames 21

9 Interface between LLC and MAC 21
9.1 Services 21
9.2 Time and time triggering 21
9.2.1 Description 21
9.2.2 Time base 21
9.2.3 Time reference point 21
9.2.4 Event generation 22
9.3 Disabling automatic retransmission 22
9.3.1 Retransmission of frames 22
9.4 Message time stamping 22

10 Description of MAC sub-layer 22
10.1 General 22
10.2 Services of MAC sub-layer 22
10.2.1 Service description 22
10.2.2 Service primitives specification 23
10.3 Functional model of MAC sub-layer architecture 27
10.3.1 Capability 27
10.3.2 Frame transmission 27
10.3.3 Frame reception 28
10.4 Structure of MAC frames 29
10.4.1 Description 29
10.4.2 Specification of MAC DF 29
10.4.3 Specification of MAC RF 34
10.4.4 Specification of EF 34
10.4.5 Specification of OF 35
10.4.6 Specification of inter-frame space 36
10.5 Frame coding 37
10.6 Frame acknowledgement 37
10.7 Frame validation 37
10.8 Order of bit transmission 38
10.9 Medium access method 39
10.9.1 General 39
10.9.2 Multi-master 39
10.9.3 Bus access 40
10.9.4 Bus integration state 40
10.9.5 Protocol exception event 40
10.9.6 Transmission of MAC frames 40
10.9.7 Content-based arbitration 40
10.9.8 Frame priority 41
10.9.9 Collision resolution 41
10.9.10 Disabling of frame formats 41
10.10 MAC data consistency 41
10.11 Error detection 41
10.12 Error signalling 42
10.13 Overload signalling 43
10.14 Bus monitoring 44
10.15 Restricted operation 44

11 PLspecification 44
11.1 General and functional modelling 44
11.2 Services of PL 44
11.2.1 Description 44
11.2.2 PCS_Data.Request 45
11.2.3 PCS_Data.Indicate 45
11.2.4 PCS_Status.Transmitter 45
11.2.5 PCS_Status.Receiver 45

11.3 PCS specification 45
11.3.1 Bit encoding/decoding 45
11.3.2 Synchronization 50
11.3.3 Transmitter delay compensation 52
11.4 AUI specification 54
11.4.1 General 54
11.4.2 PCS to PMA messages 55
11.4.3 PMA to PCS message 55

12 Description of supervisor FCE 55
12.1 Fault confinement 55
12.1.1 Objectives 55
12.1.2 Strategies 55
12.1.3 Fault confinement interface specification 56
12.1.4 Rules of fault confinement 58
12.1.5 Network start-up 60
12.2 Bus failure management 60

Annex A (informative) Additional Information 61

Bibliography 65