

# DIN EN ISO 15118-3:2016-08 (E)

## Road vehicles - Vehicle to grid Communication interface - Part 3: Physical and data link layer requirements (ISO 15118-3:2015); English version EN ISO 15118-3:2016

---

| <b>Contents</b>   |  | Page      |
|---|--|-----------|
| <b>Foreword</b> .....   |  | <b>v</b>  |
| <b>Introduction</b> .....   |  | <b>vi</b> |
| <b>1 Scope</b> .....  |  | <b>1</b>  |
| <b>2 Normative references</b> .....                                   |  | <b>1</b>  |
| <b>3 Terms and definitions</b> .....                                  |  | <b>1</b>  |
| <b>4 Symbols and abbreviated terms</b> .....                          |  | <b>4</b>  |
| <b>5 Conventions</b> .....  |  | <b>5</b>  |
| 5.1 Definition of OSI based services .....                            |  | 5         |
| 5.2 Requirement structure .....                                       |  | 5         |
| 5.3 Normative references convention .....                             |  | 5         |
| <b>6 System architecture</b> .....                                    |  | <b>6</b>  |
| 6.1 Communication layers overview .....                               |  | 6         |
| 6.2 Definition of high-level communication and basic signalling ..... |  | 7         |
| 6.2.1 Basic signalling .....  |  | 7         |
| 6.2.2 High-level communication .....                                  |  | 7         |
| 6.3 Identification requirements .....                                 |  | 8         |
| 6.4 System requirements .....   |  | 8         |
| 6.4.1 Overview .....  |  | 8         |
| 6.4.2 EVSE .....  |  | 8         |
| 6.4.3 EV .....  |  | 9         |
| 6.5 Configuration of a low-layer communication module .....           |  | 10        |
| <b>7 Connection coordination</b> .....                                |  | <b>10</b> |
| 7.1 General .....   |  | 10        |
| 7.2 Overview .....  |  | 10        |
| 7.3 Plug-in phase .....   |  | 17        |
| 7.3.1 EVSE side .....   |  | 17        |
| 7.3.2 EV side .....   |  | 17        |
| 7.4 Initialization phase .....  |  | 17        |
| 7.5 Loss of communication .....                                       |  | 18        |
| 7.5.1 EVSE side .....   |  | 18        |
| 7.5.2 EV side .....   |  | 18        |
| 7.6 Sleep mode and wake-up .....                                      |  | 19        |
| 7.6.1 Entering the sleep mode .....                                   |  | 19        |
| 7.6.2 Wake-up .....   |  | 19        |
| 7.6.3 During a charge pause .....                                     |  | 20        |
| 7.7 Plug-out phase .....  |  | 20        |
| <b>8 Timings and constants</b> .....                                  |  | <b>21</b> |
| <b>9 Matching EV — EVSE process</b> .....                             |  | <b>22</b> |
| 9.1 Overview .....  |  | 22        |
| 9.2 Initialization of matching process .....                          |  | 24        |
| 9.3 Discovery of the connected low-layer communication module .....   |  | 24        |
| 9.4 Validation of matching decision .....                             |  | 25        |
| 9.5 Set-up a logical network .....                                    |  | 27        |
| 9.6 Leave the logical network .....                                   |  | 27        |
| 9.7 Error handling .....  |  | 27        |

**10 EMC requirements .....27**

**11 Signal coupling .....27**

**12 Layer 2 interfaces .....28**

    12.1 Overview .....28

    12.2 Data SAP .....28

    12.3 Data link control SAP to layer 3 .....28

**Annex A (normative) HomePlug Green PHY on control pilot line .....30**

**Annex B (informative) IEEE 1901.2 G3-PLC profile on control pilot line .....72**

**Bibliography .....79**