

ISO 6624-4:2016-02 (E)

Internal combustion engines - Piston rings - Part 4: Half keystone rings made of steel

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Overview	1
4	Ring types and designation examples	1
4.1	Type HK -- Straight faced half keystone ring 7°	1
4.1.1	General features	1
4.1.2	Designation	2
4.2	Type HKB -- Barrel faced half keystone ring 7°	2
4.2.1	General features	2
4.2.2	Designation	4
4.3	Type HKBA -- Asymmetrical Barrel faced half keystone ring 7° (not recommended for nitrided rings of code NT)	4
4.3.1	General features	4
4.3.2	Designation	6
5	Common features	6
5.1	Type HK, HKB and HKBA -- Half keystone rings	6
5.1.1	Nitrided rings (not recommended for HKBA rings with Nitrided code NT)	6
5.1.2	PVD rings	6
5.1.3	Chromium plated or spray coated rings	7
5.2	Type HK, HKB and HKBA rings -- Outside and inside rounded edges	7
5.3	Type HK, HKB and HKBA rings (fully faced and inlaid) -- Plating/coating thickness	8
5.4	Type HK, HKB and HKBA rings -- Nitrided case depth	9
6	Force factors	10
7	Dimensions and forces	10
Annex A (normative)	Calculation of measurement width h3 of half keystone rings	19
Bibliography		20