

ISO 12156-1:2016-02 (E)

Diesel fuel - Assessment of lubricity using the high-frequency reciprocating rig (HFRR) - Part 1: Test method

| Contents | | Page |
|------------------------------------------------------------|----------------------------------------|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 2 |
| 5 | Reagents and materials | 2 |
| 6 | Apparatus | 3 |
| 7 | Sampling | 5 |
| 8 | Preparation and calibration | 6 |
| 8.1 | Preparation of apparatus | 6 |
| 8.1.1 | Test plates and balls | 6 |
| 8.1.2 | Hardware | 6 |
| 8.2 | Calibration and correction | 6 |
| 8.2.1 | Temperature | 6 |
| 8.2.2 | Frequency | 6 |
| 8.2.3 | Stroke length | 6 |
| 8.2.4 | Test duration | 6 |
| 8.2.5 | Test rig performance | 6 |
| 9 | Test procedure | 7 |
| 10 | Measurement of wear scar | 8 |
| 10.1 | General | 8 |
| 10.2 | Method "A" -- Digital camera | 8 |
| 10.3 | Method "B" -- Visual observation | 8 |
| 11 | Test results | 8 |
| 12 | Precision | 9 |
| 12.1 | General | 9 |
| 12.2 | Repeatability, r | 9 |
| 12.3 | Reproducibility, R | 9 |
| 13 | Test report | 9 |
| Annex A (informative) Measurement of HFRR wear scars | | 11 |
| Bibliography | | 15 |