

# ISO 27145-4:2016-04 (E)

## Road vehicles - Implementation of World-Wide Harmonized On-Board Diagnostics (WWH-OBD) communication requirements - Part 4: Connection between vehicle and test equipment

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>2</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>3.2</b>	<b>Abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Conventions .....</b>	<b>3</b>
<b>5</b>	<b>Document overview .....</b>	<b>3</b>
<b>6</b>	<b>Vehicle and external test equipment connection requirements .....</b>	<b>4</b>
<b>6.1</b>	<b>Overview .....</b>	<b>4</b>
<b>6.2</b>	<b>Data link independent requirements .....</b>	<b>5</b>
<b>6.3</b>	<b>Support of only one WWH-OBD-compliant external test equipment at a time .....</b>	<b>5</b>
<b>7</b>	<b>Wired CAN connection based on ISO 15765-4 .....</b>	<b>5</b>
<b>7.1</b>	<b>Network scenario requirements .....</b>	<b>5</b>
<b>7.2</b>	<b>Initialization sequence .....</b>	<b>5</b>
<b>7.4</b>	<b>Application layer -- DoCAN .....</b>	<b>5</b>
<b>7.4.1</b>	<b>General .....</b>	<b>5</b>
<b>7.4.2</b>	<b>Diagnostic protocol communication types .....</b>	<b>6</b>
<b>7.4.3</b>	<b>Maximum number of WWH-OBD servers/ECUs .....</b>	<b>6</b>
<b>7.4.4</b>	<b>Diagnostic protocol timing parameters .....</b>	<b>6</b>
<b>7.4.5</b>	<b>External test equipment logical addresses .....</b>	<b>6</b>
<b>7.4.6</b>	<b>Server/ECU logical addressing .....</b>	<b>6</b>
<b>7.5</b>	<b>Presentation layer .....</b>	<b>6</b>
<b>7.6</b>	<b>Session layer .....</b>	<b>7</b>
<b>7.7</b>	<b>Transport layer .....</b>	<b>7</b>
<b>7.7.1</b>	<b>General information .....</b>	<b>7</b>
<b>7.7.2</b>	<b>Mapping of data-link-independent service primitives onto DoCAN data-link-dependent service primitives .....</b>	<b>7</b>
<b>7.7.3</b>	<b>Mapping of T_PDU onto N_PDU for message transmission .....</b>	<b>7</b>
<b>7.8</b>	<b>Network layer .....</b>	<b>8</b>
<b>7.9</b>	<b>Data link layer .....</b>	<b>8</b>
<b>7.10</b>	<b>Physical layer .....</b>	<b>8</b>
<b>7.11</b>	<b>Diagnostic connector .....</b>	<b>8</b>
<b>8</b>	<b>Wired Ethernet connection based on ISO 13400 .....</b>	<b>8</b>
<b>8.1</b>	<b>Network scenario requirements .....</b>	<b>8</b>
<b>8.2</b>	<b>Initialization sequence .....</b>	<b>9</b>
<b>8.4</b>	<b>Application layer -- DoIP .....</b>	<b>13</b>
<b>8.4.1</b>	<b>General .....</b>	<b>13</b>
<b>8.4.2</b>	<b>Diagnostic protocol communication types .....</b>	<b>13</b>

8.4.3	Maximum number of WWH-OBd servers/ECUs .....	14
8.4.4	Diagnostic protocol timing parameters .....	14
8.4.5	External test equipment logical addresses .....	14
8.4.6	Server/ECU logical addressing .....	14
8.5	Presentation layer .....	14
8.6	Session layer .....	14
8.7	Transport layer .....	15
8.7.1	General information .....	15
8.7.2	Mapping of data-link-independent service primitives onto the Internet Protocol data-link- dependent service primitives .....	15
8.7.3	Mapping of T_PDU onto DoIP_PDU for message transmission .....	15
8.8	Network layer .....	16
8.9	Data link layer .....	16
8.10	Physical layer .....	16
8.11	Diagnostic connector .....	16
Bibliography .....		17