

ISO 10924-5:2016-04 (E)

Road vehicles - Circuit breakers - Part 5: Circuit breakers with bolt with rated voltage of 450 V

| Contents | | Page |
|---|---|------|
| Foreword | | iv |
| 1 Scope | 1 | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Marking, labelling and colour coding | | 1 |
| 5 Tests and requirements | | 2 |
| 5.1 General | | 2 |
| 5.1.1 General test conditions | | 2 |
| 5.1.2 Test sequence plan | | 2 |
| 5.1.3 Test cable sizes | | 3 |
| 5.2 Voltage drop | | 4 |
| 5.2.1 Purpose | | 4 |
| 5.2.2 Tests | | 4 |
| 5.2.3 Requirements | | 4 |
| 5.3 Maximum housing temperature | | 5 |
| 5.4 Environmental conditions | | 5 |
| 5.5 Operating time-rating | | 5 |
| 5.5.1 Purpose | | 5 |
| 5.5.2 Tests | | 5 |
| 5.5.3 Requirements | | 5 |
| 5.6 Current steps | | 5 |
| 5.7 No current trip and reset temperature | | 5 |
| 5.8 Absolute breaking capacity | | 6 |
| 5.8.1 Tests | | 6 |
| 5.8.2 Requirements | | 6 |
| 5.9 Breaking capacity | | 6 |
| 5.9.1 Tests | | 6 |
| 5.9.2 Requirements | | 6 |
| 5.10 Strength of terminals | | 6 |
| 5.10.1 Tests | | 6 |
| 5.10.2 Requirements | | 7 |
| 5.11 Endurance | | 7 |
| 5.11.1 Tests | | 7 |
| 5.11.2 Requirements | | 7 |
| 5.12 Dielectric strength | | 7 |
| 5.12.1 Tests | | 7 |
| 5.12.2 Requirement | | 7 |
| 5.13 Pulse test | | 7 |
| 5.13.1 Purpose | | 7 |
| 5.13.2 Test | | 7 |
| 5.13.3 Requirement | | 8 |
| 6 Dimensions and designation example | | 9 |
| Bibliography | | 10 |