

ISO 15765-4:2016-04 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 4: Requirements for emissions-related systems

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Symbols	2
3.3	Abbreviated terms	2
4	Conventions	3
5	Document overview	3
6	External test equipment initialization sequence	4
6.1	General	4
6.2	Baudrate validation procedure	7
6.2.1	BaudrateRecord	7
6.2.2	Baudrate validation	7
6.2.3	External test equipment error detection provisions	9
6.3	CAN identifier validation procedure	9
6.3.1	CAN identifier validation procedure OBD	9
6.3.2	CAN identifier validation procedure WWH-OBD	11
7	Application layer	13
8	Session layer	14
9	Transport protocol layer	14
10	Network layer	14
10.1	General	14
10.2	Network layer parameters	14
10.2.1	Timing parameter values	14
10.2.2	Definition of Flow Control parameter values	15
10.2.3	Maximum number of legislated OBD/WWH-OBD ECUs	16
10.3	Addressing formats	17
10.3.1	Normal and fixed addressing format	17
10.3.2	Functional addressing	17
10.3.3	Physical addressing	17
10.4	CAN identifier requirements	18
10.4.1	External test equipment	18
10.4.2	Legislated OBD/WWH-OBD server/ECU	18
10.5	Mapping of diagnostic addresses	19
10.5.1	Legislated OBD/WWH-OBD CAN identifiers	19
10.5.2	11 bit CAN identifiers	19
10.5.3	29 bit CAN identifiers	20
10.6	Support of ECUNAME reporting	21

11	Data link layer	21
12	Physical layer	21
12.1	General	21
12.2	External test equipment baudrates	21
12.3	External test equipment CAN bit timing	21
12.3.1	CAN bit timing parameter values	21
12.3.2	Nominal baudrate 250 kBit/s	22
12.3.3	Nominal baudrate 500 kBit/s	23
12.4	External test equipment	23
12.4.1	General	23
12.4.2	CAN interface	24
12.4.3	External test equipment cable	26
	Bibliography	27