

# ISO 1161:2016-07 (E)

## Series 1 freight containers - Corner and intermediate fittings - Specifications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Dimensional requirements .....</b>	<b>1</b>
<b>3.1</b>	<b>General .....</b>	<b>1</b>
<b>3.2</b>	<b>Detailed dimensional and manufacturing requirements .....</b>	<b>1</b>
<b>4</b>	<b>Strength requirements .....</b>	<b>2</b>
<b>5</b>	<b>Design requirements .....</b>	<b>2</b>
<b>5.1</b>	<b>Loading .....</b>	<b>2</b>
<b>5.1.1</b>	<b>General .....</b>	<b>2</b>
<b>5.1.2</b>	<b>Stacking .....</b>	<b>3</b>
<b>5.1.3</b>	<b>Lifting .....</b>	<b>3</b>
<b>5.1.4</b>	<b>Longitudinal restraint .....</b>	<b>3</b>
<b>5.1.5</b>	<b>Vertical restraint .....</b>	<b>3</b>
<b>5.1.6</b>	<b>Lashing and securing .....</b>	<b>3</b>
<b>5.1.7</b>	<b>Misgather (offset loading) .....</b>	<b>4</b>
<b>5.2</b>	<b>Compulsory features .....</b>	<b>4</b>
<b>6</b>	<b>Minimum bearing area -- Top and bottom corner and intermediate fittings .....</b>	<b>4</b>
<b>7</b>	<b>Corner and intermediate fitting marking .....</b>	<b>4</b>
<b>8</b>	<b>Required tests .....</b>	<b>5</b>
<b>8.1</b>	<b>General .....</b>	<b>5</b>
<b>8.2</b>	<b>Casting defect checks .....</b>	<b>5</b>
<b>8.3</b>	<b>Tests .....</b>	<b>5</b>
	<b>Annex A (normative) Testing methodology .....</b>	<b>17</b>
	<b>Annex B (informative) Typical examples of twistlock lifting devices .....</b>	<b>22</b>
	<b>Bibliography .....</b>	<b>24</b>