

# ISO 17987-1:2016-08 (E)

## Road vehicles - Local Interconnect Network (LIN) - Part 1: General information and use case definition

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Conventions .....</b>	<b>3</b>
<b>5</b>	<b>Use case overview and principles .....</b>	<b>3</b>
<b>5.1</b>	<b>Basic principles for use case definition .....</b>	<b>3</b>
<b>5.2</b>	<b>Use case clusters .....</b>	<b>3</b>
<b>6</b>	<b>LIN communication system use case definition .....</b>	<b>3</b>
<b>6.1</b>	<b>UC 1 LIN master task cluster .....</b>	<b>3</b>
<b>6.1.1</b>	<b>UC 1.1 Generate LIN frame header .....</b>	<b>3</b>
<b>6.2</b>	<b>UC 2 LIN slave task cluster .....</b>	<b>4</b>
<b>6.2.1</b>	<b>UC 2.1 Break/sync byte field sequence detector .....</b>	<b>4</b>
<b>6.2.2</b>	<b>UC 2.2 LIN frame processor .....</b>	<b>4</b>
<b>6.2.3</b>	<b>UC 2.3 Slave node configuration .....</b>	<b>4</b>
<b>6.2.4</b>	<b>UC 2.4 Slave error status reporting .....</b>	<b>5</b>
<b>6.2.5</b>	<b>UC 2.5 Diagnostic slave node capabilities .....</b>	<b>5</b>
<b>6.3</b>	<b>UC 3 LIN communication protocol cluster .....</b>	<b>6</b>
<b>6.3.1</b>	<b>UC 3.1 Synchronization .....</b>	<b>6</b>
<b>6.3.2</b>	<b>UC 3.2 Checksum .....</b>	<b>6</b>
<b>6.3.3</b>	<b>UC 3.3 Slave bitrate detection .....</b>	<b>6</b>
<b>6.4</b>	<b>UC 4 LIN physical layer cluster .....</b>	<b>7</b>
<b>6.4.1</b>	<b>UC 4.1 Performance in non-operation supply voltage range .....</b>	<b>7</b>
<b>6.4.2</b>	<b>UC 4.2 Loss of supply voltage .....</b>	<b>7</b>
<b>6.5</b>	<b>UC 5 LIN network management .....</b>	<b>7</b>
<b>6.5.1</b>	<b>UC 5.1 LIN cluster network management .....</b>	<b>7</b>
<b>Bibliography .....</b>		<b>8</b>