

# ISO 17987-4:2016-09 (E)

## Road vehicles - Local Interconnect Network (LIN) - Part 4: Electrical physical layer (EPL) specification 12 V/24 V

---

| <b>Contents</b>              |  | <b>Page</b> |
|------------------------------|--|-------------|
| Foreword .....               |  | iv          |
| Introduction .....           |  | v           |
| <b>1</b>                     | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>                     | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>                     | <b>Terms, definitions, symbols and abbreviated terms .....</b>                   | <b>1</b>    |
| <b>3.1</b>                   | <b>Terms and definitions .....</b>   | <b>1</b>    |
| <b>3.2</b>                   | <b>Symbols .....</b>   | <b>2</b>    |
| <b>3.3</b>                   | <b>Abbreviated terms .....</b>   | <b>5</b>    |
| <b>4</b>                     | <b>Conventions .....</b>   | <b>6</b>    |
| <b>5</b>                     | <b>Electrical physical layer requirements .....</b>                              | <b>6</b>    |
| <b>5.1</b>                   | <b>Bit rate deviation .....</b>  | <b>6</b>    |
| <b>5.1.1</b>                 | <b>12 V LIN systems: Parameters .....</b>  | <b>6</b>    |
| <b>5.1.2</b>                 | <b>24 V LIN systems: Parameters .....</b>  | <b>7</b>    |
| <b>5.2</b>                   | <b>Timing requirements .....</b>   | <b>9</b>    |
| <b>5.2.1</b>                 | <b>Bit timing .....</b>  | <b>9</b>    |
| <b>5.2.2</b>                 | <b>Synchronization procedure .....</b>   | <b>9</b>    |
| <b>5.2.3</b>                 | <b>Bit sample timing .....</b>   | <b>9</b>    |
| <b>5.3</b>                   | <b>Line driver/receiver .....</b>  | <b>11</b>   |
| <b>5.3.1</b>                 | <b>General configuration .....</b>   | <b>11</b>   |
| <b>5.3.2</b>                 | <b>Definition of supply voltages for the physical interface .....</b>            | <b>11</b>   |
| <b>5.3.3</b>                 | <b>Signal specification .....</b>  | <b>12</b>   |
| <b>5.3.4</b>                 | <b>12 V LIN systems: Electrical parameters .....</b>                             | <b>13</b>   |
| <b>5.3.5</b>                 | <b>24 V LIN systems: Electrical parameters .....</b>                             | <b>17</b>   |
| <b>5.3.6</b>                 | <b>Line characteristics .....</b>  | <b>20</b>   |
| <b>5.3.7</b>                 | <b>12 V LIN systems: performance in non-operation supply voltage range .....</b> | <b>20</b>   |
| <b>5.3.8</b>                 | <b>24 V LIN systems: performance in non-operation supply voltage range .....</b> | <b>21</b>   |
| <b>5.3.9</b>                 | <b>Performance during fault modes .....</b>                                      | <b>21</b>   |
| <b>5.3.10</b>                | <b>ESD/EMI compliance .....</b>  | <b>21</b>   |
| <b>Annex A (informative)</b> | <b>LIN peripheral interface design considerations .....</b>                      | <b>22</b>   |
| <b>Bibliography .....</b>    |  | <b>27</b>   |