

# ISO 13296:2016-12 (E)

## Diesel engines - High-pressure fuel injection pipe assemblies - General requirements and dimensions

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Dimensions and tolerances .....</b>	<b>1</b>
<b>5</b>	<b>Cleanliness .....</b>	<b>3</b>
<b>6</b>	<b>Minimum bend radii .....</b>	<b>3</b>
<b>7</b>	<b>Pipe end connections .....</b>	<b>3</b>
7.1	General .....	3
7.2	Types of connection ends .....	3
7.3	Pipe end assembly for integral 60° female cones .....	4
7.4	Pipe end assembly for fabricated 60° female cones .....	6
7.5	Bore entrance configuration .....	8
<b>8</b>	<b>Assembly clamps .....</b>	<b>8</b>
<b>9</b>	<b>External coatings .....</b>	<b>9</b>
<b>10</b>	<b>Operating pressure .....</b>	<b>9</b>
<b>11</b>	<b>Pipe inside diameter .....</b>	<b>9</b>
<b>12</b>	<b>Tightening torque and sealing performance .....</b>	<b>9</b>
<b>13</b>	<b>Packaging and identification .....</b>	<b>9</b>
<b>Annex A (normative) Operating pressure .....</b>		<b>10</b>
<b>Bibliography .....</b>		<b>11</b>