ISO 6624-1:2017-04 (E)

Internal combustion engines - Piston rings - Part 1: Keystone rings made of cast iron

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative reference 1

3 Termsanddefinitions 1

4 Overview 1

5 Ring types and designation examples 1
5.1 Type T -- Straight faced keystone ring 6° 1
5.1.1 General features 1
5.1.2 Designation 2
5.2 Type TB -- Symmetrical barrel faced keystone ring 6° 2
5.2.1 General features 2
5.2.2 Designation 4
5.3 Type TBA -- Asymmetrical barrel faced keystone ring 6° 4
5.3.1 General features 4
5.3.2 Designation 5
5.4 Type TM -- Taper faced keystone ring 6° 5
5.4.1 General features 5
5.4.2 Designation 6
5.5 Type K -- Straight faced keystone ring 15° 7
5.5.1 General features 7
5.5.2 Designation 7
5.6 Type KB -- Symmetrical barrel faced keystone ring 15° 7
5.6.1 General features 7
5.6.2 Designation 8
5.7 Type KBA -- Asymmetrical barrel faced keystone ring 15° 8
5.7.1 General features 8
5.7.2 Designation 9
5.8 Type KM -- Taper faced keystone ring 15° 9
5.8.1 General features 9
5.8.2 Designation 10

6 Common features 11
6.1 Type T, TB, TBA, TM, K, KB, KBA, KM rings -- Inside chamfered edges (KI) 11
6.2 Type T, TB, TBA, TM, K, KB, KBA, KM rings (positive twist type) internal bevel or internal step top side 11
6.3 Type TM or KM rings with partly cylindrical machined (LM) or lapped (LP) peripheral surface 12
6.4 Type T, TB, TBA, TM, K, KB, KBA, KM rings -- Plating/coating configuration 13
6.4.1 Uncoated rings 13
6.4.2 Chromium plated, PVD coated or spray coated rings 14

7 Force factors 16

8 Dimensions 16

Bibliography 24