

ISO 12619-10:2017-08 (E)

Road vehicles - Compressed gaseous hydrogen (CGH₂) and hydrogen/natural gas blends fuel system components - Part 10: Pressure relief device (PRD)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Marking	2
5	Construction and assembly	3
6	Tests	3
6.1	Applicability	3
6.2	Hydrostatic strength	4
6.2.1	Housing	4
6.2.2	Fusible material	4
6.3	Leakage	4
6.4	Bending moment	5
6.5	Continued operation	5
6.5.1	Test procedure	5
6.5.2	Requirements	5
6.6	Accelerated life	5
6.6.1	General	5
6.6.2	Test procedure	5
6.6.3	Accelerated-life test temperature	6
6.6.4	Requirements	6
6.7	Benchtop activation	6
6.7.1	General	6
6.7.2	Thermally activated relief devices	6
6.7.3	Parallel-combination relief devices	7
6.8	Thermal cycling	7
6.8.1	Test procedure	7
6.8.2	Requirements	8
6.9	Condensate-corrosion resistance	8
6.9.1	Test procedure	8
6.9.2	Test solution	8
6.10	Flow capacity	8
6.10.1	General	8
6.10.2	Test procedure	8
6.11	Impact due to drop and vibration	9
6.11.1	Impact due to drop	9
6.11.2	Vibration	9
7	Production batch inspection and acceptance testing	9
Annex A (normative)	Determination of fusible material yield temperature and PRD activation temperature	10
Bibliography		12