

ISO 16673:2017-09 (E)

Road vehicles - Ergonomic aspects of transport information and control systems - Occlusion method to assess visual demand due to the use of in-vehicle systems

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Measurement procedures | 4 |
| 4.1 | Set-up | 4 |
| 4.2 | Vision and occlusion intervals | 4 |
| 4.3 | Task timing | 5 |
| 4.4 | Exclusion of trials | 6 |
| 5 | Assessing visual demand | 6 |
| 5.1 | Selection of tasks | 6 |
| 5.2 | Participants | 6 |
| 5.3 | Training | 6 |
| 5.4 | Test trials | 7 |
| 5.5 | Experimental plan | 7 |
| 5.6 | Calculation of visual demand metrics | 8 |
| 5.6.1 | General | 8 |
| 5.6.2 | Calculating TSOT | 8 |
| 5.6.3 | Calculating R | 9 |
| 5.6.4 | Interpretation of results | 10 |
| Annex A (informative) System response delay | | 11 |
| Annex B (informative) Surrogate driving task as a primary task | | 14 |
| Bibliography | | 15 |