

ISO 19377:2017-11 (E)

Heavy commercial vehicles and buses - Emergency braking on a defined path - Test method for trajectory measurement

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Variables	2
6 Measuring equipment	3
7 Test conditions	3
7.1 General	3
7.2 Test track and ambient conditions	4
7.3 Test vehicle	4
7.3.1 General vehicle condition	4
7.3.2 Loading condition	4
7.3.3 Number of test runs	4
8 Test methods	4
8.1 Test method for braking straight ahead	4
8.1.1 Initial driving condition	4
8.1.2 Definition of the desired path and track	4
8.1.3 System intervention	5
8.2 Test method for braking in a constant radius curve	5
8.2.1 Initial driving condition	5
8.2.2 Definition of the desired path and track	5
8.2.3 System intervention	6
9 Data evaluation and presentation of results	6
9.1 General	6
9.2 Characteristic values	7
9.2.1 Maximum path deviation, DP,max	7
9.2.2 Maximum rear axle path deviation, DPR,max	7
9.2.3 Maximum trailer path deviation, DPT,max	8
9.2.4 Deceleration at full braking	8
9.2.5 Maximum articulation angle(s) (optional)	8
9.2.6 Corrective steering action, H,C (for closed-loop test)	8
9.2.7 Indication of leaving the desired track (optional)	8
Annex A (normative) Test report -- General data and test conditions	9
Annex B (informative) Example of test reports	10
Bibliography	12