

# ISO 19377:2017-11 (E)

## Heavy commercial vehicles and buses - Emergency braking on a defined path - Test method for trajectory measurement

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Variables .....</b>	<b>2</b>
<b>6</b>	<b>Measuring equipment .....</b>	<b>3</b>
<b>7</b>	<b>Test conditions .....</b>	<b>3</b>
7.1	General .....	3
7.2	Test track and ambient conditions .....	4
7.3	Test vehicle .....	4
7.3.1	General vehicle condition .....	4
7.3.2	Loading condition .....	4
7.3.3	Number of test runs .....	4
<b>8</b>	<b>Test methods .....</b>	<b>4</b>
8.1	Test method for braking straight ahead .....	4
8.1.1	Initial driving condition .....	4
8.1.2	Definition of the desired path and track .....	4
8.1.3	System intervention .....	5
8.2	Test method for braking in a constant radius curve .....	5
8.2.1	Initial driving condition .....	5
8.2.2	Definition of the desired path and track .....	5
8.2.3	System intervention .....	6
<b>9</b>	<b>Data evaluation and presentation of results .....</b>	<b>6</b>
9.1	General .....	6
9.2	Characteristic values .....	7
9.2.1	Maximum path deviation, DP,max .....	7
9.2.2	Maximum rear axle path deviation, DPR,max .....	7
9.2.3	Maximum trailer path deviation, DPT,max .....	8
9.2.4	Deceleration at full braking .....	8
9.2.5	Maximum articulation angle(s) (optional) .....	8
9.2.6	Corrective steering action, H,C (for closed-loop test) .....	8
9.2.7	Indication of leaving the desired track (optional) .....	8
<b>Annex A (normative)</b>	<b>Test report -- General data and test conditions .....</b>	<b>9</b>
<b>Annex B (informative)</b>	<b>Example of test reports .....</b>	<b>10</b>
<b>Bibliography .....</b>		<b>12</b>