ISO 15118-5:2018-02 (E)

Road vehicles - Vehicle to grid communication interface - Part 5: Physical layer and data link layer conformance test

Contents

Foreword ... vii

Introduction ... viii

1 Scope ... 1

2 Normative references ... 2

3 Terms and definitions ... 2

4 Symbols (and abbreviated terms) ... 7

5 Conventions ... 8
5.1 Requirement structure ... 8
5.2 Test system description ... 8

6 Test architecture reference model ... 8
6.1 General information ... 8
6.2 Platform adapter interface ... 9
6.3 SUT adapter interfaces ... 9
6.4 Codecs ... 10

7 Test suite conventions ... 10
7.1 General information ... 10
7.2 Test suite structure (TSS) ... 10
7.3 Test profiles ... 12
7.3.1 Test configurations ... 12
7.3.2 Components and ports ... 13
7.3.3 Protocol implementation conformance statement (PICS) definition ... 14
7.3.4 Protocol implementation extra information for testing (PIXIT) definition ... 15
7.3.5 Test control ... 17

Table 12 — SECC AC PICS/PIXIT configuration ... 17

Table 13 — SECC DC PICS/PIXIT configuration ... 18

Table 14 — EVCC AC PICS/PIXIT configuration ... 19

Table 15 — EVCC DC PICS/PIXIT configuration ... 20
7.4 Test suite identifiers ... 22
7.4.1 Module identifiers ... 22
7.4.2 Test case identifiers ... 22
7.4.3 Template identifiers ... 24
7.4.4 Function identifiers ... 25
7.4.5 Timer identifiers ... 26
7.4.6 PICS/PIXIT identifiers ... 26
7.4.7 Verdict identifiers ... 27
7.5 Test suite coverage ... 27

Table 29 — ATS coverage of requirements in ISO 15118-3 ... 28

Table 30 — Groups for a simplified TC Id representation (see Table 29) ... 46
7.6 Test case description ... 56
7.7 Test case specification ... 57
7.7.1 Data types ... 57
7.7.2 Templates ... 57
7.7.3 Timeouts and timers ... 58
7.7.4 Library functions ... 58

7.7.5 Test case modelling 58
7.7.6 SLAC Message handling for different SUT types 59
7.7.7 IEC 61851-1 PWM event handling and control 59
7.7.8 Data link status control functionality 61
7.7.9 EIM status control functionality 61
7.7.10 Transmission power limitation functionality 61
7.7.11 Attenuator injection functionality 61

8 Test case descriptions for ISO 15118-3 HPGP PLC signal measurement 62
8.1 General information 62
8.2 Test case for PLC signal measurement for ISO 15118-3 62
8.3 SECC + PLC bridge test cases 62
8.3.1 SECC test cases for CmSlacParm 62
8.3.2 SECC test cases for AttenuationCharacterization 69
8.3.3 SECC test cases for CmValidate 79
8.3.4 SECC test cases for CmSlacMatch 86
8.3.5 SECC test cases for PLCLinkStatus 98
8.3.6 SECC test cases for CmAmpMap 110
8.4 EVCC + PLC bridge test cases 114
8.4.1 EVCC test cases for CmSlacParm 114
8.4.2 EVCC test cases for AttenuationCharacterization 122
8.4.3 EVCC test cases for CmValidate 130
8.4.4 EVCC test cases for CmValidateOrCmSlacMatch 142
8.4.5 EVCC test cases for CmSlacMatch 142
8.4.6 EVCC test cases for PLCLinkStatus 148
8.4.7 EVCC test cases for CmAmpMap 159

Annex A (normative) Configuration specifications 164
A.1 Timer configuration 164
A.2 PICS configuration 165
A.3 PIXIT configuration 165

Annex B (normative) Control part specification 167
B.1 SECC control parts 167
B.1.1 AC specific control parts 167
B.1.2 DC specific control parts 172
B.2 EVCC control parts 177
B.2.1 AC specific control parts 177
B.2.2 DC specific control parts 181

Annex C (normative) Test-case specifications for 15118-3 186
C.1 SECC + PLC bridge test cases 186
C.1.1 SECC test cases for CmSlacParm 186
C.1.2 SECC test cases for AttenuationCharacterization 190
C.1.3 SECC test cases for CmValidate 197
C.1.4 SECC test cases for CmSlacMatch 202
C.1.5 SECC test cases for PLCLinkStatus 209
C.1.6 SECC test cases for CmAmpMap 212
C.2 EVCC + PLC bridge test cases 214

C.2.1 EVCC test cases for CmSlacParm 214
C.2.2 EVCC test cases for AttenuationCharacterization 219
C.2.3 EVCC test cases for CmValidate 224
C.2.4 EVCC test cases for CmValidateOrCmSlacMatch 232
C.2.5 EVCC test cases for CmSlacMatch 232
C.2.6 EVCC test cases for PLCLinkStatus 236
C.2.7 EVCC test cases for CmAmpMap 244
Annex D (normative) Function specifications for supporting test execution 248
D.1 Configuration functions 248
D.2 Pre-condition functions 250
D.2.1 SECC + PLC bridge functions 250
D.2.2 EVCC + PLC bridge functions 253
D.3 Post-condition functions 256
D.3.1 SECC + PLC bridge functions 256
D.3.2 EVCC + PLC bridge functions 257
D.4 Library functions 257
Annex E (normative) Function specifications for 15118-3 259
E.1 SECC + PLC bridge functions 259
E.1.1 SECC functions for CmSlacParm 259
E.1.2 SECC functions for AttenuationCharacterization 266
E.1.3 SECC functions for CmValidate 281
E.1.4 SECC functions for CmSlacMatch 298
E.1.5 SECC functions for CmSetKey 303
E.1.6 SECC functions for PLCLinkStatus 304
E.1.7 SECC functions for CmAmpMap 313
E.2 EVCC + PLC bridge functions 318
E.2.1 EVCC functions for CmSlacParm 319
E.2.2 EVCC functions for AttenuationCharacterization 324
E.2.3 EVCC functions for CmValidate 346
E.2.4 EVCC functions for CmValidateOrCmSlacMatch 367
E.2.5 EVCC functions for CmSlacMatch 370
E.2.6 EVCC functions for CmSetKey 373
E.2.7 EVCC functions for PLCLinkStatus 373
E.2.8 EVCC functions for CmAmpMap 379
Annex F (normative) Template specifications for 15118-3 385
F.1 Common + PLC bridge templates 385
F.1.1 CMN templates for CmSlacParm 386
F.1.2 CMN templates for CmStartAttenCharInd 387

F.1.3 CMN templates for CmMnbcSoundInd 387
F.1.4 CMN templates for CmAttenCharRsp 387
F.1.5 CMN templates for CmValidate 388
F.1.6 CMN templates for CmSlacMatch 389
F.1.7 CMN templates for CmSetKey 390
F.1.8 CMN templates for CmAmpMap 391
F.1.9 CMN templates for CmNwStats 394
F.2 SECC + PLC bridge templates 394
F.2.1 SECC templates for CmAttenCharInd 395
F.3 EVCC + PLC bridge templates 395
F.3.1 EVCC templates for CmAttenProfileInd 395
F.3.2 EVCC templates for CmAttenCharInd 395
Annex G (normative) Data type definitions 397
G.1 Data types for PICS 397
G.2 Data types for PIXIT 397
G.3 Data types for SLAC 398
Bibliography 403