

ISO 20762:2018 (E)

Electrically propelled road vehicles — Determination of power for propulsion of hybrid electric vehicle

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols and abbreviated terms |
| 5 | Test condition |
| 5.1 | Test instrumentation |
| 5.1.1 | Chassis dynamometer |
| 5.1.2 | Test room |
| 5.1.3 | Cooling fan |
| 5.2 | Measurement |
| 5.2.1 | Measurement items and accuracy |
| 5.2.2 | Measurement frequency |
| 6 | Test procedure |
| 6.1 | General |
| 6.2 | Preparation of chassis dynamometer |
| 6.2.1 | Roller |
| 6.2.2 | Tire slippage |
| 6.2.3 | Chassis dynamometer warm-up |
| 6.2.4 | Chassis dynamometer control |
| 6.3 | Preparation of vehicle |
| 6.4 | Preparation of measurement devices |
| 6.5 | Initial charge of RESS |
| 6.6 | Vehicle soak |
| 6.7 | Vehicle installation |
| 6.8 | Test sequence |
| 6.8.1 | General |
| 6.8.2 | Vehicle conditioning |
| 6.8.3 | RESS adjustment |
| 6.8.4 | Vehicle operation |
| 6.8.5 | Pedal operation |
| 6.8.6 | End of vehicle running |
| 6.9 | Calculation of HEV system power |
| 6.9.1 | General |
| 6.9.2 | Calculation for TP1 |
| 6.9.3 | Calculation for TP2 |
| 6.9.3.1 | Calculation |
| 6.9.3.2 | ICE power correction factors |
| 6.9.3.3 | Corrected HEV system power for test procedure option 2 (TP2) |
| 6.10 | Determination of maximum HEV system power |
| 7 | Test report |
| 7.1 | General |
| 7.2 | Calculated values based on measured data |
| 7.3 | Measured data |

- 7.4 Environmental data
 - 7.5 Assumed values
 - 7.6 General vehicle data based on the manufacturer's information (informative)
- Annex A (informative) Examples for gearbox system efficiency factor (includes gearbox and differential) at maximum HEV system power**
- A.1 General
 - A.2 Series hybrid-electric vehicle (Series HEV)
 - A.3 Parallel hybrid-electric vehicle (Parallel HEV)
 - A.4 Power split hybrid-electric vehicle (power split HEV)

Page count: 17