ISO 1496-2:2018 (E)

Series 1 freight containers — Specification and testing — Part 2: Thermal containers

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Classification

5 Marking

6 Dimensions and ratings

- 6.1 External dimensions
- 6.2 Internal dimensions
- 6.3 Ratings

7 Design requirements

- 7.1 General
- 7.2 Corner fittings
- 7.3 Base structure
- 7.4 End structure
- 7.5 Side wall structure
- 7.6 Walls
- 7.7 Door opening
- 7.8 Sanitary and taint-free requirements
- 7.9 Requirements for optional features
- 7.9.1 Fork-lift pockets
- 7.9.2 Gooseneck tunnels
- 7.9.3 Drains
- 7.9.4 Water connections
- 7.9.5 Picture frames
- 7.9.6 Modified/controlled atmospheres
- 7.9.7 Fresh air ventilation control
- 7.9.8 Humidity control
- 7.9.9 Load line
- 7.9.10 Floor
- 7.9.11 Air circulation

8 Testing

- 8.1 General
- 8.2 Test No. 13 — Airtightness test
- 8.2.1 General
- 8.2.2 Procedure
- 8.2.3 Requirements
- 8.3 Test No. 14 — Heat leakage test
- 8.3.1 General
- 8.3.2 Procedure
- 8.3.3 Heat leakage calculation
- 8.3.4 Requirements
- 8.4 Test No. 15 a) — Test of the performance of a thermal container under refrigeration by a mechanical refrigeration unit (MRU)
- 8.4.1 General

8.4.2 Test conditions
8.4.3 Test procedure
8.4.4 Requirements
8.5 Test No. 15 b) — Functional test of a thermal container at high ambient temperatures while being cooled by a mechanical refrigeration unit (MRU)
8.5.1 General
8.5.2 The thermal container shall be equipped with instruments for the measurement of:
8.5.3 Test conditions
8.5.4 Test procedure
8.5.5 Requirements
8.6 Test No. 15 c) — Energy consumption of a thermal container at defined ambient temperatures while being cooled by a mechanical refrigeration unit (MRU)
8.6.1 General
8.6.2 The thermal container shall be equipped with instruments for the measurement of:
8.6.3 Test conditions
8.6.4 Test procedure
8.6.5 Requirements
8.7 Test No. 16 — Strength of mounting devices for removable equipment (where fitted)
8.7.1 General
8.7.2 Test No. 16 a) — Vertical loading
8.7.2.1 General
8.7.2.2 Procedure
8.7.2.3 Requirements
8.7.3 Test No. 16 b) — Horizontal loading
8.7.3.1 General
8.7.3.2 Procedure
8.7.3.3 Requirements

9 Electrical aspects of thermal containers

9.1 General
9.2 General requirements for standard voltage equipment
9.3 Remote condition monitoring

Annex A (normative) Requirements for cooling water connections

Annex B (informative) Picture frames

Annex C (normative) Air temperature measurement points

Annex D (normative) Phase connections to container plugs and sockets

Annex E (normative) Electric plug and socket, four-pin, 380/440 V, 50/60 Hz, 32 A

Annex F (informative) Electrical power supplies for thermal containers (9.2)

Annex G (normative) General requirements for 220 V and dual voltage equipment

G.1 220 V equipment
G.2 Dual voltage equipment

Annex H (informative) MRU Nose Mounted Frame (Optional Backup Generator Set)

Annex I (informative) Ageing of polyurethane foam

I.1 General
I.2 Background
I.3 Determination of accelerated aged value of thermal conductivity
I.4 Calculation method for the determination of the thermal transmittance of a panel (Ud,s)
I.5 Calculating ageing
I.6 Conclusion

Page count: 45