ISO 11452-2:2019 (E)

Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy — Part 2: Absorber-lined shielded enclosure

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Test conditions

5 Test location

6 Test apparatus and instrumentation

- 6.1 General
- 6.2 Measuring equipment
- 6.3 Stimulation and monitoring of DUT

7 Test set-up for DUT powered by an unshielded power system

- 7.1 Ground plane
- 7.2 Power supply and AN
- 7.3 Location of DUT
- 7.4 Location of test harness
- 7.5 Location of load simulator
- 7.6 Location of field generating device (antenna)

8 Test setup for DUT powered by a shielded power system

- 8.1 Ground plane
- 8.2 Power supply and AN
- 8.3 Location of DUT
- 8.4 Location of test harness
- 8.5 Location of load simulator
- 8.6 Location of field generating device (antenna)

9 Test method

- 9.1 General
- 9.2 Test plan
- 9.3 Test procedure
- 9.3.1 General
- 9.3.2 Substitution method
- 9.3.3 Field calibration
- 9.3.4 DUT test
- 9.4 Test report

Annex A (informative) Remote/local grounding

- A.1 DUT remotely grounded
- A.2 DUT locally grounded

Annex B (informative) Function performance status classification (FPSC)

- B.1 General
- B.2 Classification of test severity level
- B.3 Example of FPSC application using test severity levels