

# ISO 19642-6:2019 (E)

## Road vehicles — Automotive cables — Part 6: Dimensions and requirements for 600 V a.c. or 900 V d.c. and 1 000 V a.c. or 1 500 V d.c. single core aluminium conductor cables

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
|         | Introduction  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Specifications  |
| 4.1     | General test conditions   |
| 4.2     | Safety concerns   |
| 4.3     | Voltage ratings   |
| 4.4     | Temperature classes   |
| 4.5     | Conductor material  |
| 4.6     | Conductors  |
| 4.7     | Insulation thickness  |
| 4.8     | Cable outside diameter  |
| 4.9     | Representative conductor sizes for testing                        |
| 4.10    | Reference and requirements for the tests according to ISO 19642-2 |
| 5       | Requirements  |
| 5.1     | General   |
| 5.2     | Dimensional tests   |
| 5.2.1   | Cable outside diameter  |
| 5.2.2   | Insulation thickness  |
| 5.2.3   | Conductor diameter  |
| 5.2.4   | Cross sectional area  |
| 5.2.5   | In-process cable outside diameter                                 |
| 5.3     | Electrical tests  |
| 5.3.1   | Conductor resistance  |
| 5.3.2   | Determination of temperature coefficients                         |
| 5.3.3   | Withstand voltage   |
| 5.3.4   | Withstand voltage after environmental testing                     |
| 5.3.5   | Insulation faults   |
| 5.3.6   | Insulation volume resistivity                                     |
| 5.4     | Mechanical tests  |
| 5.4.1   | Strip force   |
| 5.4.2   | Abrasion  |
| 5.4.2.1 | General   |
| 5.4.2.2 | Sandpaper abrasion test   |
| 5.4.2.3 | Scrape abrasion test  |
| 5.4.3   | Breaking force of the finished cable                              |
| 5.4.4   | Cyclic bending  |
| 5.4.5   | Flexibility   |
| 5.5     | Environmental tests   |
| 5.5.1   | Test specimen preparation and winding tests                       |
| 5.5.2   | Long term heat ageing, 3 000 h at temperature class rating        |
| 5.5.3   | Short term heat ageing, 240 h at temperature class rating +25 °C  |
| 5.5.4   | Thermal overload, 6 h at temperature class rating +50 °C          |
| 5.5.5   | Pressure test at high temperature                                 |

- 5.5.6 Shrinkage by heat
- 5.5.7 Low temperature winding
- 5.5.8 Cold impact
- 5.5.9 Temperature and humidity cycling
- 5.5.10 Resistance to hot water
- 5.5.11 Resistance to liquid chemicals
- 5.5.12 Durability of cable marking
- 5.5.13 Stress cracking resistance
- 5.5.14 Resistance to ozone
- 5.5.15 Resistance to flame propagation

**Annex A (informative) ISO conductor sizes, number of strands and strand diameter**

- A.1 Conductors — Existing stranding configurations
- A.2 Conductors — Preferred stranding configurations

**Annex B (informative) Harness and cable colours**

Page count: 18