ISO/FDIS 20934ISO 20934:2019 (E)

Road vehicles — Fuse-links with axial terminals for use in 48V networks — Types SF36-70V, SF51-70V and SF56-70VRoad vehicles — Fuse-links with axial terminals for use in 48V networks — Types SF36-70V, SF51-70V and SF56-70V

Contents

Foreword

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Marking, labelling and colour coding

5 Design and test requirements

5.1 General
5.1.1 General test conditions
5.1.2 General performance requirements
5.1.3 General fuse-link requirements
5.1.4 Test sequence
5.1.5 Test cable size
5.2 Voltage drop
5.2.1 Purpose
5.2.2 Test
5.2.3 Requirement
5.3 Current cycling
5.3.1 Purpose
5.3.2 Test
5.3.3 Requirement
5.4 Environmental conditions
5.4.1 Purpose
5.4.2 Mechanical Shock and Vibration test
5.4.3 Climatic loads
5.4.4 Chemical loads
5.4.5 Temperature shock
5.4.6 Requirement
5.5 Operating time rating
5.5.1 Purpose
5.5.2 Test
5.5.3 Requirement
5.6 Current steps
5.6.1 Purpose
5.6.2 Test
5.6.3 Requirement
5.7 Breaking capacity
5.7.1 Purpose
5.7.2 Test
5.7.3 Requirement
5.8 Mechanical stability
5.8.1 Purpose
5.8.2 Test
5.8.3 Requirement
5.9 Insulation resistance
5.9.1 Purpose

5.9.2 Test
5.9.3 Requirement
5.10 Cold resistance
5.10.1 Purpose
5.10.2 Test
5.10.3 Requirement
5.11 Overload test
5.11.1 Purpose
5.11.2 Test
5.11.3 Requirement

6 Dimensions and examples of designation

6.1 Type SF36-70V
6.1.1 Dimensions bolt-down
6.1.2 Dimensions clinchable
6.2 Type SF51-70V
6.3 Type SF56-70V
6.4 Designation example

7 Test fixture

7.1 SF36-70V
7.2 SF51-70V
7.3 SF56-70V

1 Scope

2 Normative references

3 Terms and definitions

4 Marking, labelling and colour coding

5 Design and test requirements

5.1 General
5.1.1 General test conditions
5.1.2 General performance requirements
5.1.3 General fuse-link requirements
5.1.4 Test sequence
5.1.5 Test cable size
5.2 Voltage drop
5.2.1 Purpose
5.2.2 Test
5.2.3 Requirement
5.3 Current cycling
5.3.1 Purpose
5.3.2 Test
5.3.3 Requirement
5.4 Environmental conditions
5.4.1 Purpose
5.4.2 Mechanical Shock and Vibration test
5.4.3 Climatic loads
5.4.4 Chemical loads
5.4.5 Temperature shock
5.4.6 Requirement
5.5 Operating time rating
5.5.1 Purpose
5.5.2 Test
5.5.3 Requirement
5.6 Current steps
5.6.1 Purpose
5.6.2 Test
5.6.3 Requirement
5.7 Breaking capacity
5.7.1 Purpose

5.7.2 Test
5.7.3 Requirement
5.8 Mechanical stability
5.8.1 Purpose
5.8.2 Test
5.8.3 Requirement
5.9 Insulation resistance
5.9.1 Purpose
5.9.2 Test
5.9.3 Requirement
5.10 Cold resistance
5.10.1 Purpose
5.10.2 Test
5.10.3 Requirement
5.11 Overload test
5.11.1 Purpose
5.11.2 Test
5.11.3 Requirement

6 Dimensions and examples of designation

6.1 Type SF36-70V
6.1.1 Dimensions bolt-down
6.1.2 Dimensions clinchable
6.2 Type SF51-70V
6.3 Type SF56-70V
6.4 Designation example

7 Test fixture

7.1 SF36-70V
7.2 SF51-70V
7.3 SF56-70V

Annex A (informative) Optional tests

A.1 Retightening torque and setting behaviour
A.1.1 Purpose
A.1.2 Test
A.1.3 Requirement
A.2 I2t-value
A.2.1 Purpose
A.2.2 Test
A.2.3 Requirement
A.3 Derating of the fuse-link
A.3.1 Purpose
A.3.2 Test
A.3.3 Requirement

Annex A (informative) Optional tests

A.1 Retightening torque and setting behaviour
A.1.1 Purpose
A.1.2 Test
A.1.3 Requirement
A.2 I2t-value
A.2.1 Purpose
A.2.2 Test
A.2.3 Requirement
A.3 Derating of the fuse-link
A.3.1 Purpose
A.3.2 Test
A.3.3 Requirement

Page count: 0 20