ISO 20766-9:2019 (E)

Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 9: Pressure relieve device (PRD)

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Markings

5 Construction and assembly

6 Tests

- 6.1 Applicability
- 6.2 Hydrostatic strength
- 6.3 Leakage
- 6.4 Bending moment
- 6.5 Continued operation
- 6.5.1 Test procedure
- 6.5.2 Requirements
- 6.6 Accelerated life
- 6.6.1 General
- 6.6.2 Test procedure
- 6.6.3 Accelerated-life test temperature
- 6.6.4 Requirements
- 6.7 Benchtop activation
- 6.7.1 General
- 6.7.2 Thermally-activated relief devices
- 6.7.2.1 Test setup
- 6.7.2.2 Test procedure
- 6.7.2.3 Requirements
- 6.8 Thermal cycling
- 6.8.1 Test procedure
- 6.8.2 Requirements
- 6.9 Condensate-corrosion resistance
- 6.9.1 Test procedure
- 6.9.2 Test solution
- 6.10 Flow capacity
- 6.10.1 General
- 6.10.2 Test procedure

7 Production batch inspection and acceptance testing

Annex A (normative) Determination of fusible material yield temperature and PRD activation temperature

- A.1 General
- A.2 Fusible material yield temperature
- A.2.1 Sample selection
- A.2.2 Test setup
- A.2.3 Test procedure
- A.2.4 Requirements
- A.3 PRD activation temperature determination
- A.3.1 Differential scanning calorimetry (DSC) method