

# ISO 19072-1:2019-08 (E)

## Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 1: Pocket interface definition

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	<b>Scope .....</b>	<b>1</b>
2	<b>Normative references .....</b>	<b>1</b>
3	<b>Terms and definitions .....</b>	<b>1</b>
4	<b>Dimensional features -- Squib holder interface including male contacts .....</b>	<b>2</b>
5	<b>Material characteristics .....</b>	<b>4</b>
5.1	<b>Material specifications for male contacts .....</b>	<b>4</b>
5.2	<b>Contacts and short circuit areas of the male contacts specifications .....</b>	<b>4</b>
<b>Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly .....</b>		<b>5</b>
<b>Annex B (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly .....</b>		<b>6</b>
<b>Annex C (normative) Undercut geometry for the alternative material of the pyrotechnic device/initiator harness connector assembly .....</b>		<b>7</b>
<b>Bibliography .....</b>		<b>8</b>