

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Usage of LTE in ITS
5.1	LTE features used in ITS
5.2	General access to the Internet
5.3	Device-to-device communications (D2D)
5.4	Vehicle-to-everything communications (V2X)
5.5	Implementation guidelines
6	General requirements
6.1	LTE basics
6.1.1	LTE-V2X
6.1.2	Supported LTE modes of operation
6.1.2.1	Overview
6.1.2.2	PC5 interface communications
6.1.2.3	Uu interface communications
6.2	ITS station
6.2.1	Station and communication architecture
6.2.2	Service access points
6.2.2.1	General
6.2.2.2	Communications service access points
6.2.2.3	Management service access points
6.2.2.4	Security service access points
6.2.3	Hybrid communications support
7	Communication interface protocol stack
7.1	Physical layer
7.2	Data link layer
7.2.1	Basic behaviour
7.2.2	Data link layer communication addresses
7.2.3	Identification of higher layer protocols
7.3	Communication adaptation sub-layer
8	Communication interface management
8.1	General management
8.2	Management adaptation entity
8.2.1	LTE-V2X parameters and I-Parameters
8.2.2	LTE-V2X management commands and MI-SAP commands and requests
9	Procedures
9.1	Communication interface procedures
9.1.1	Transmit procedure
9.1.2	Receive procedure

9.2	Management procedures
9.2.1	Cross-CI prioritization
9.2.2	Operational mode
9.2.3	LTE-V2X MAC address mapping
9.2.3.1	LTE-V2X SideLink communication
9.2.3.2	LTE-V2X Uu communication
9.2.3.3	Overview
9.2.4	CI connection procedure
9.2.5	CI state management
10	Conformance
11	Test methods
Annex A	(normative) Communication interface parameters
A.1	General
A.2	I-Parameters specific to ITS-LTE-V2X
A.3	Default values of I-Parameters
Annex B	(normative) MI-COMMANDs
B.1	General
B.2	Required functionality
Annex C	(normative) MI-REQUESTs
C.1	General
C.2	Required functionality
Annex D	(normative) ASN.1 definitions
D.1	Overview
D.2	Module ITSltcv2x
D.3	Definitions to be added in ISO 21218
Annex E	(informative) CI state transitions

Page count: 27