

# ISO 17987-8:2019-10 (E)

## Road vehicles - Local Interconnect Network (LIN) - Part 8: Electrical physical layer (EPL) specification: LIN over DC powerline (DC-LIN)

---

| <b>Contents</b>       |  | <b>Page</b> |
|-----------------------|--|-------------|
| Foreword .....        |  | iv          |
| Introduction .....    |  | v           |
| <b>1</b>              | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>              | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>              | <b>Terms, definitions, symbols, and abbreviated terms .....</b>                                    | <b>1</b>    |
| 3.1                   | Terms and definitions .....  | 2           |
| 3.2                   | Symbols and abbreviated terms .....  | 2           |
| <b>4</b>              | <b>Electrical physical layer requirements .....</b>  | <b>5</b>    |
| 4.1                   | General .....  | 5           |
| 4.2                   | Transmitter characteristics .....  | 6           |
| 4.2.1                 | Transmit signal specification .....  | 6           |
| 4.2.2                 | Byte field modulation scheme .....   | 7           |
| 4.2.3                 | Break field modulation scheme .....  | 14          |
| 4.2.4                 | Wake-up signal modulation scheme .....   | 15          |
| 4.3                   | Timing requirements .....  | 18          |
| 4.3.1                 | Bit rate tolerance .....   | 18          |
| 4.3.2                 | Bit timing .....   | 19          |
| 4.3.3                 | Bit sample timing .....  | 19          |
| 4.3.4                 | TXD assert timeout event .....   | 19          |
| 4.3.5                 | Delay between transmitted byte field (DC-LIN node A) and received byte field (DC-LIN node A) ..... | 19          |
| 4.3.6                 | Delay between transmitted byte field (DC-LIN node A) and received byte field (DC-LIN node B) ..... | 19          |
| 4.4                   | Receiver characteristics .....   | 21          |
| 4.5                   | Electrical parameters .....  | 21          |
| 4.5.1                 | General configuration -- Coupling to the DC powerline .....  | 21          |
| 4.5.2                 | Signal specification .....   | 22          |
| 4.5.3                 | Line-out monitoring .....  | 23          |
| 4.5.4                 | ESD compliance .....   | 28          |
| 4.6                   | Communication in the presence of faults .....  | 28          |
| Annex A (informative) | DC-LIN EPL peripheral interface design considerations .....  | 30          |
| Annex B (normative)   | DC-LIN EPL conformance test plan .....   | 31          |
| Bibliography .....    |  | 56          |