

ISO 8820-8:2019-10 (E)

Road vehicles - Fuse-links - Part 8: Fuse-links with bolt-in contacts (Type H and J) with rated voltage of 450 V

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Marking, labelling and colour coding	1
5	Tests and requirements	2
5.1	General	2
5.1.1	Test criteria	2
5.1.2	Test sequence	2
5.1.3	Test cable sizes	2
5.2	Voltage drop	3
5.2.1	Tests	3
5.2.2	Requirements	3
5.3	Transient current cycling	4
5.3.1	Test	4
5.3.2	Requirements	4
5.4	Environmental conditions	4
5.5	Operating time-rating	4
5.5.1	Test	4
5.5.2	Requirement	5
5.6	Current steps	5
5.7	Breaking capacity	5
5.7.1	Test	5
5.7.2	Requirement	5
5.8	Strength of terminals	5
5.8.1	Test	5
5.8.2	Requirements	6
5.9	Temperature rise	6
5.9.1	Test	6
5.9.2	Requirement	6
5.10	Resistance against temperature shock	6
5.10.1	Test	6
5.10.2	Requirement	7
6	Dimensions	7
6.1	Type H	7
6.2	Type J	8
7	Test fixture for fuse-links Type H and Type J	9
Annex A (informative)	Classification	10
Bibliography		11