

# ISO 19072-2:2019-12 (E)

## Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Functional characteristics of mated connectors .....</b>	<b>2</b>
4.1	General .....	2
4.2	Visual examination .....	2
4.3	Mating and unmating .....	2
4.4	Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer .....	3
4.4.1	Test .....	3
4.4.2	Requirements .....	4
4.5	Mechanical strength of the retainer in the squib holder .....	5
4.5.1	Test .....	5
4.5.2	Requirements .....	5
4.6	Combination of temperature/humidity/vibration .....	6
4.6.1	Test .....	6
4.6.2	Requirements .....	8
4.7	Coding .....	9
4.7.1	Test .....	9
4.7.2	Requirements .....	9
4.8	Polarisation .....	9
4.8.1	Test .....	9
4.8.2	Requirements .....	9
4.9	Contact resistance (voltage drop), millivolt test .....	9
4.9.1	Test .....	9
4.9.2	Requirements .....	11
4.10	Insulation resistance .....	11
4.11	Withstand voltage .....	11
4.12	Thermal ageing .....	11
4.13	Opening and closing of the short-circuit .....	11
4.14	Short-circuit resistance .....	12
4.14.1	Test .....	12
4.14.2	Requirements .....	13
4.15	Rapid change of temperature (thermal shock) .....	13
4.16	Chemical fluids .....	13
<b>5</b>	<b>Test sequences .....</b>	<b>13</b>
<b>Annex A (normative)</b>	<b>Sealed variant of the pyrotechnic device/initiator harness connector assembly .....</b>	<b>15</b>
<b>Annex B (normative)</b>	<b>Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly .....</b>	<b>17</b>
<b>Annex C (normative)</b>	<b>Variant without retainer of the pyrotechnic device/initiator harness connector assembly .....</b>	<b>19</b>
<b>Bibliography .....</b>		<b>20</b>