

ISO 19072-2:2019-12 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Functional characteristics of mated connectors	2
4.1	General	2
4.2	Visual examination	2
4.3	Mating and unmating	2
4.4	Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer	3
4.4.1	Test	3
4.4.2	Requirements	4
4.5	Mechanical strength of the retainer in the squib holder	5
4.5.1	Test	5
4.5.2	Requirements	5
4.6	Combination of temperature/humidity/vibration	6
4.6.1	Test	6
4.6.2	Requirements	8
4.7	Coding	9
4.7.1	Test	9
4.7.2	Requirements	9
4.8	Polarisation	9
4.8.1	Test	9
4.8.2	Requirements	9
4.9	Contact resistance (voltage drop), millivolt test	9
4.9.1	Test	9
4.9.2	Requirements	11
4.10	Insulation resistance	11
4.11	Withstand voltage	11
4.12	Thermal ageing	11
4.13	Opening and closing of the short-circuit	11
4.14	Short-circuit resistance	12
4.14.1	Test	12
4.14.2	Requirements	13
4.15	Rapid change of temperature (thermal shock)	13
4.16	Chemical fluids	13
5	Test sequences	13
Annex A (normative)	Sealed variant of the pyrotechnic device/initiator harness connector assembly	15
Annex B (normative)	Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly	17
Annex C (normative)	Variant without retainer of the pyrotechnic device/initiator harness connector assembly	19
Bibliography		20