ISO 19072-2:2019-12 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods a nd general performance requirements

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Functional characteristics of mated connectors 2
4.1 General 2
4.2 Visual examination 2
4.3 Mating and unmating 2
4.4 Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer 3
4.4.1 Test 3
4.4.2 Requirements 4
4.5 Mechanical strength of the retainer in the squib holder 5
4.5.1 Test 5
4.5.2 Requirements 5
4.6 Combination of temperature/humidity/vibration 6
4.6.1 Test 6
4.6.2 Requirements 8
4.7 Coding 9
4.7.1 Test 9
4.7.2 Requirements 9
4.8 Polarisation 9
4.8.1 Test 9
4.8.2 Requirements 9
4.9 Contact resistance (voltage drop), millivolt test 9
4.9.1 Test 9
4.9.2 Requirements 11
4.10 Insulation resistance 11
4.11 Withstand voltage 11
4.12 Thermal ageing 11
4.13 Opening and closing of the short-circuit 11
4.14 Short-circuit resistance 12
4.14.1 Test 12
4.14.2 Requirements 13
4.15 Rapid change of temperature (thermal shock) 13
4.16 Chemical fluids 13

5 Test sequences 13

Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly 15

Annex B (normative) Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly 17

Annex C (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly 19

Bibliography 20