

# ISO 19072-2:2019-12 (E)

## Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

---

Contents		Page
Foreword .....		iv
Introduction .....		v
1 Scope .....		1
2 Normative references .....		1
3 Terms and definitions .....		1
4 Functional characteristics of mated connectors .....		2
4.1 General .....		2
4.2 Visual examination .....		2
4.3 Mating and unmating .....		2
4.4 Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer .....		3
4.4.1 Test .....		3
4.4.2 Requirements .....		4
4.5 Mechanical strength of the retainer in the squib holder .....		5
4.5.1 Test .....		5
4.5.2 Requirements .....		5
4.6 Combination of temperature/humidity/vibration .....		6
4.6.1 Test .....		6
4.6.2 Requirements .....		8
4.7 Coding .....		9
4.7.1 Test .....		9
4.7.2 Requirements .....		9
4.8 Polarisation .....		9
4.8.1 Test .....		9
4.8.2 Requirements .....		9
4.9 Contact resistance (voltage drop), millivolt test .....		9
4.9.1 Test .....		9
4.9.2 Requirements .....		11
4.10 Insulation resistance .....		11
4.11 Withstand voltage .....		11
4.12 Thermal ageing .....		11
4.13 Opening and closing of the short-circuit .....		11
4.14 Short-circuit resistance .....		12
4.14.1 Test .....		12
4.14.2 Requirements .....		13
4.15 Rapid change of temperature (thermal shock) .....		13
4.16 Chemical fluids .....		13
5 Test sequences .....		13
Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly .....		15
Annex B (normative) Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly .....		17
Annex C (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly .....		19
Bibliography .....		20